Cudy AC1300 White Power over Ethernet (PoE)

Modelis: AP1300

Gamintojas: CUDY

EAN: 6971690792022

Prekės kodas: 366704

42.99€

Compatible operating systems: Windows, MAC OS, NetWare, UNIX, Linux | Flash memory: 16 MB | Cabling technology: 10/100/1000Base-T(X) | Rate limiting: Yes | Output voltage: 12 V | Height: 232 mm | Operating relative humidity (H-H): 10 - 90% | Antenna type: Internal | 5 GHz: Yes | Processor frequency: 880 MHz | Operating temperature (T-T): 0 - 40 °C | Maximum data transfer rate (2.4 GHz): 300 Mbit/s | Ethernet LAN (RJ-45) ports: 1 | Mounting kit: Yes | Antenna direction type: Omni-directional | Placement: Ceiling, Wall | Reset button: Yes | Antennas quantity: 4 | Power consumption (max): 11 W | Quick start guide: Yes | DC-in jack: Yes | 2.4 GHz: Yes | Power over Ethernet (PoE): Yes | Security algorithms: WPA2-PSK | MAC address filtering: Yes | Networking standards: IEEE 802.11b | Width: 232 mm | Networking standards: IEEE 802.3at | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.11ac | Ethernet LAN data rates: 100 | Built-in processor: Yes | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.3ab | Ethernet LAN data rates: 10 | MIMO: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Internal memory: 128 MB | Networking standards: IEEE 802.11g | Networking standards: IEEE

802.11n | Ethernet LAN data rates: 1000 Mbit/s | Product colour: White | AC adapter included: Yes | Networking standards: IEEE 802.3af | Depth: 57.1 mm | IP address filtering: Yes | MIMO type: Multi User MIMO | Quantity per pack: 1 pc(s) | Output current: 1 A | LED indicators: Yes | Maximum data transfer rate (5 GHz): 867 Mbit/s | Power over Ethernet (PoE) type supported: Passive PoE | Warnings: Electronic products should be recycled at specialist electronic waste collection facilities. | Warnings: Avoid direct contact with water. | 6 GHz: No | Band steering: Yes | DC voltage range: 24 - 57 V | Compliance certificates: CE | Sustainability compliance: Yes | Service Set Identifier (SSID) features: Multiple SSIDs | Fit AP mode features: Mesh networking | Warnings: Do not expose to prolonged moisture.