



TP-Link 16-Port Gigabit Easy Smart Network Switch



Modelis: TL-SG1016DE

Gamintojas: TP-LINK

EAN: 6935364021269

Prekės kodas: 366712

76.99€

Compatible operating systems: Windows | Product colour: Black | 10G support: No | User guide: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | AC input frequency: 50/60 Hz | Operating relative humidity (H-H): 10 - 90% | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.3u | Number of VLANs: 32 | Rack mount kit: Yes | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Housing material: Metal | Power over Ethernet (PoE): No | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Width: 284 mm | Package weight: 1.91 kg | Cables included: AC | Store-and-forward: Yes | Switch layer: L2 | Resource CD: Yes | Power supply included: Yes | Maximum cable length: 100 m | Jumbo frames support: Yes | Form factor: 1U | Package width: 250 mm | IGMP snooping: Yes | Operating temperature (T-T): 0 - 40 °C | Rate limiting: Yes | Sustainability certificates: CE | Rack mounting: Yes | Sustainability compliance: Yes | Cable types supported: Cat6 | Sustainability certificates: Federal Communications Commission (FCC) | Gigabit Ethernet (copper) ports quantity: 16 | Jumbo frames: 9000 | Link aggregation: Yes | Cable types supported: Cat5 | Sustainability

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

išsijyiant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

certificates: RoHS | Height: 44 mm | Power source: AC | Basic switching RJ-45 Ethernet ports quantity: 16 | Copper ethernet cabling technology: 1000BASE-T | Copper ethernet cabling technology: 100BASE-TX | Copper ethernet cabling technology: 100BASE-T | Package height: 80 mm | Package type: Box | LED indicators: Yes | Heat dissipation: 34.52 BTU/h | AC input voltage: 100 - 240 V | VLAN support: Yes | Number of queues: 4 | Switch type: Managed | Power connector: AC-in jack | Power consumption (max): 19.15 W | Switching capacity: 32 Gbit/s | Forwarding rate: 23.8 Mpps | Package depth: 400 mm | Flow control support: Yes | Auto MDI/MDI-X: Yes | MAC address table: 8000 entries | Auto-negotiation: Yes | Packet buffer memory: 0.512 MB | Port mirroring: Yes | Broadcast storm control: Yes | Cable types supported: Cat3 | Depth: 180 mm | Virtual LAN features: Tagged VLAN | Virtual LAN features: Port-based VLAN

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903