



# TP-Link Omada ES208G network switch Managed L2 Gigabit Ethernet (10/100/1000) Black



Modelis: ES208G

Gamintojas: TP-LINK

EAN: 1210002600668

Prekės kodas: 366713

---

## 42.99€

---

Networking standards: IEEE 802.1ab | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3i | Networking standards: IEEE 802.3at | Web-based management: Yes | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | LED indicators: Yes | Input current: 0.6 A | Product colour: Black | Operating temperature (T-T): -5 - 45 °C | AC adapter included: Yes | Package type: Box | Firmware upgradeable: Yes | Operating relative humidity (H-H): 10 - 90% | DHCP features: DHCP client | Gigabit Ethernet (copper) ports quantity: 8 | Link aggregation: Yes | Jumbo frames: 15000 | Surge protection: Yes | DC input voltage: 5 V | Power supply included: Yes | Store-and-forward: Yes | Switch layer: L2 | IGMP snooping: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Fanless: Yes | Basic switching

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | 10G support: No | Number of VLANs: 32 | User guide: Yes | Power source: DC | Wall mountable: Yes | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Mean time between failures (MTBF): 1141726 h | Heat dissipation: 9.09 BTU/h | Switch type: Managed | Flash memory: 64 MB | Basic switching RJ-45 Ethernet ports quantity: 8 | VLAN support: Yes | Jumbo frames support: Yes | Loop protection: Yes | Power over Ethernet (PoE): No | Storage relative humidity (H-H): 5 - 90% | Width: 158 mm | Rack mounting: No | Power consumption (max): 2.7 W | Height: 25.4 mm | Switching capacity: 16 Gbit/s | Surge protection voltage: 6 kV | Forwarding rate: 11.9 Mpps | Port mirroring: Yes | MAC address table: 8000 entries | Auto-negotiation: Yes | Depth: 100.7 mm | Virtual LAN features: Port-based VLAN | Stackable: No | Virtual LAN features: Tagged VLAN | Cloud-managed: Yes | Auto MDI/MDI-X: Yes | Packet buffer memory: 4 MB | Virtual LAN features: MTU VLAN | Unified static configuration: Yes | Fast leave: Yes | Zero Touch Provisioning (ZTP): Yes | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC)

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903