



TP-Link Omada ES228GMP network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Modelis: ES228GMP

Gamintojas: TP-LINK

EAN: 1210002600989

Prekės kodas: 366714

349.99€

Certification: FCC, CE, RoHS | Unified static configuration: Yes | Fast leave: Yes | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | Product colour: Black | AC input frequency: 50/60 Hz | Operating temperature (T-T): -5 - 45 °C | Storage relative humidity (H-H): 5 - 90% | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Ethernet LAN data rates: 10,100,1000 Mbit/s | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Power consumption (max): 454.8 W |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Operating relative humidity (H-H): 10 - 90% | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | LED indicators: Yes | Networking standards: IEEE 802.1ab | AC input voltage: 100 - 240 V | Power over Ethernet (PoE): Yes | Networking standards: IEEE 802.3u | Firmware upgradeable: Yes | Noise level: 46.2 dB | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.3i | Web-based management: Yes | Networking standards: IEEE 802.3af | Quick start guide: Yes | Networking standards: IEEE 802.3z | Total Power over Ethernet (PoE) budget: 384 W | Depth: 330 mm | Surge protection: Yes | Flash memory: 64 MB | Copper ethernet cabling technology: 10BASE-T | Copper ethernet cabling technology: 100BASE-X | Mean time between failures (MTBF): 224143 h | Copper ethernet cabling technology: 1000BASE-T | Housing material: Metal | Power over Ethernet (PoE) power per port: 30 W | Manual: Yes | Jumbo frames support: Yes | VLAN support: Yes | Power supply included: Yes | Power source: AC | SFP module slots quantity: 2 | Auto MDI/MDI-X: Yes | Height: 44 mm | Number of fans: 2 fan(s) | Cables included: AC | Switching capacity: 56 Gbit/s | Copper ethernet cabling technology: 1000BASE-X | Width: 440 mm | Rack mounting: Yes | Store-and-forward: Yes | Number of VLANs: 32 | Broadcast storm control: Yes | 10G support: No | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Virtual LAN features: Tagged VLAN | Power over Ethernet plus (PoE+) ports quantity: 24 | Forwarding rate: 41.66 Mpps | Link aggregation: Yes | Jumbo frames: 15000 | Gigabit Ethernet (copper) ports quantity: 26 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Multicast support: Yes | Virtual LAN features: MTU VLAN | Rack mount kit: Yes | Fanless: No | Virtual LAN features: Port-based VLAN | Surge protection voltage: 6 kV | Heat dissipation: 1546.15 BTU/h | Power over Ethernet (PoE) type supported: PoE+ | Basic switching RJ-45 Ethernet ports quantity: 26 | Switch type: Managed | IGMP snooping: Yes | Packet buffer memory: 4 MB | Port mirroring: Yes | Switch layer: L2 | MAC address table: 8000 entries | Cloud-managed: Yes | DHCP features: DHCP client

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903