shopro

TP-LINK 16-Port Gigabit Rackmount Network Switch

Modelis: TL-SG1016

Gamintojas: TP-LINK

EAN: 6935364020095

Prekės kodas: 366837

70.99€

Copper ethernet cabling technology: 100BASE-TX | Copper ethernet cabling technology: 1000BASE-T | VLAN support: Yes | Copper ethernet cabling technology: 10BASE-T | User operation log: Yes | Forwarding rate: 23.8 Mpps | Static port security: Yes | Traffic shaping: Yes | Width: 440 mm | Policy-based routing: Yes | Store-and-forward: Yes | DHCP features: DHCP snooping | Switch layer: L2 | Jumbo frames: 10000 | Jumbo frames support: Yes | Rack mounting: Yes | Port mirroring: Yes | DHCP features: DHCP client | Cable types supported: Cat4 | Cable types supported: Cat3 | Head-of-line (HOL) blocking: Yes | Password protection: Yes | Switching capacity: 32 Gbit/s | Height: 44 mm | DHCP features: DHCP server | Cloud-managed: Yes | Full duplex: Yes | Traffic classification: Yes | Depth: 180 mm | IGMP snooping: Yes | System event log: Yes | Auto MDI/MDI-X: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | MAC address table: 8000 entries | Auto-negotiation: Yes | Heat dissipation: 31.6 BTU/h | Cable types supported: Cat5 | Cable types supported: Cat5e | Access Control List (ACL): Yes | Configuring Location Settings (CLI): Yes | Basic switching RJ-45 Ethernet ports quantity: 16 | Switch type: Unmanaged | IP routing: Yes | Flow control support: Yes | AC input frequency: 50/60 Hz | Operating relative humidity (H-H): 10 - 90% |

Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Storage relative humidity (H-H): 5 - 90% | Web-based management: Yes | Security algorithms: 802.1x RADIUS | LED indicators: Yes | AC input voltage: 100 - 240 V | Networking standards: IEEE 802.3u | Operating temperature (T-T): 0 - 40 °C | Networking standards: IEEE 802.3i | Networking standards: IEEE 802.3x | Ethernet LAN data rates: 100 | Product colour: Black | Power consumption (typical): 9.26 W | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 1000 Mbit/s | Ethernet LAN data rates: 800 | Ethernet LAN data rates: 480 | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes