



TP-Link Omada 300Mbps Wireless N Ceiling Mount Access Point



Modelis: EAP110

Gamintojas: TP-LINK

EAN: 6935364091620

Prekės kodas: 367428

38.99€

Receiver sensitivity: 300M: -71dBm@10% PER 150M: -75dBm@10% PER 54M: -78dBm@10% PER 11M: -93dBm@8% PER 6M: -92dBm@10% PER 1M: -96dBm@8% PER | Compliance certificates: RoHS | Compliance certificates: CE | Warnings: Avoid direct contact with water. | Warnings: Electronic products should be recycled at specialist electronic waste collection facilities. | Warnings: Do not expose to prolonged moisture. | Compliance certificates: Federal Communications Commission (FCC) | Web-based management: Yes | MAC address filtering: Yes | 2.4 GHz: Yes | Ethernet LAN data rates: 10 | Ethernet LAN data rates: 100 | Networking standards: IEEE 802.11b | 5 GHz: No | Frequency band: 2.4 - 2.4835 GHz | Networking standards: IEEE 802.1x | LED indicators: Power | AC input voltage: 24 V | Product colour: White | Maximum data transfer rate: 300 Mbit/s | Antenna type: Internal | Reset button: Yes | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Transmitting power (CE): 19 dBm | 6 GHz: No | Package height: 69 mm | Package type: Box | Antennas quantity: 2 | Quick start guide: Yes | Security algorithms: WPA2-PSK | Transmitting

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

power (FCC): 21 dBm | Security algorithms: 64-bit WEP | Security algorithms: WPA2-Enterprise | Security algorithms: SNMPv2 | Rate limiting: Yes | Sustainability compliance: Yes | Cabling technology: 10/100Base-T(X) | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Security algorithms: HTTPS | Security algorithms: 128-bit WEP | Security algorithms: SNMP | Placement: Ceiling, Wall | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | PoE adapter included: Yes | Security algorithms: SSH | Operating relative humidity (H-H): 10 - 90% | Security algorithms: 152-bit WEP | Mounting kit: Yes | Security algorithms: WPA | Quantity per pack: 1 pc(s) | Power consumption (typical): 2.8 W | Access Control List (ACL): Yes | Antenna gain level (max): 4 dBi | Height: 29.7 mm | Cables included: AC | Wireless isolation: Yes | Power over Ethernet (PoE) type supported: Passive PoE | Power over Ethernet (PoE): Yes | Width: 189.5 mm | Antenna direction type: Omni-directional | VLAN support: Yes | Number of SSID supported: 8 | Ethernet LAN (RJ-45) ports: 1 | Maximum data transfer rate (2.4 GHz): 300 Mbit/s | Package depth: 268 mm | Service Set Identifier (SSID) features: Multiple SSIDs | Syslog: Yes | Package weight: 720 g | Wi-Fi Multimedia (WMM)/(WME): Yes | Harmonized System (HS) code: 85176990 | Operating temperature (T-T): 0 - 40 °C | Package width: 246 mm | Depth: 170.5 mm | Virtual LAN features: VLAN mapping

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903