



DAHUA SD5A425GA- HNR IP CAMERA



Modelis: SD5A425GA-HNR

Gamintojas: DAHUA

EAN: 6923172545855

Prekės kodas: 367486

639.99€

Certification: CE: EN55032/EN55024/EN50130-4 FCC: Part15 subpartB, ANSI C63.4-2014
UL:UL60950-1+CAN/CSA C22.2, No.60950-1 | PoE standard: IEEE 802.3at | PoE+ support: Yes |
Warnings: The product contains electronic components do not dispose of with the normal household waste. | Warnings: Avoid direct contact with water to prevent electrical damage. | Warnings: Ensure that the product is properly installed and protected against falling. | Lens viewing angle, diagonal: 66.6°-4° | Placement supported: Outdoor | Video compression formats: H.264H | Mounting type: Ceiling | Video streaming: Yes | Video compression formats: H.264B | Lens viewing angle, vertical: 35,7 - 2° | Lens viewing angle, horizontal: 61,6 - 3,6° | Closest focusing distance: 5.4 m | Product diameter: 190 mm | Anti-flicker: Yes | DC output current: 2.5 A | DC output voltage: 24V | Camera pan control: Yes | Video motion detection: Yes | Privacy masking: Yes | Number of lenses: 1 | Camera tilt control: Yes | Night vision: Yes | Sensor type: CMOS | Camera shutter speed: 1 - 1/30000 s | International Protection (IP) code: IP67 | Video compression formats: H.264 | Maximum aperture number: 4 | Video compression formats: H.265 | Optical sensor size: 25.4 / 1.8 mm (1 / 1.8") | Region of Interest (ROI) encoding: Yes | Wide Dynamic Range (WDR): 120 dB | Bit rate: H.264: 96 kbps-14848 kbps H.265: 38 kbps-8960 kbps | Video compression formats: H.265+ | Package weight:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

8 kg | Height: 332 mm | Ethernet LAN: Yes | Angle of rotation: 360° | Highlight Compensation (HLC): Yes | Video compression formats: H.264+ | Minimum illumination: 0 lx | Operating temperature (T-T): -40 - 70 °C | Noise reduction: Yes | Day/night mode: Yes | Total megapixels: 4 MP | Ethernet interface type: Fast Ethernet | Operating relative humidity (H-H): 0 - 95% | Video compression formats: M-JPEG | Noise reduction technology: 2D NR/ 3D NR | HTTPS encryption: Yes | Storage relative humidity (H-H): 0 - 95% | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Type: IP security camera | Progressive scan: Yes | Pan range: 0 - 360° | Power consumption (max): 21 W | Fixed focal length: 13.5 cm | Maximum resolution: 2560 x 1440 pixels | Supported graphics resolutions: 1920 x 960 | Supported graphics resolutions: 352 x 240 | Supported graphics resolutions: 1280 x 720 | Power source type: DC, PoE | Supported graphics resolutions: 704 x 576 | Supported graphics resolutions: 2048 x 1536 (QXGA) | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 2560 x 1440 | Weight: 4.7 kg | Supported graphics resolutions: 352 x 288 | Connectivity technology: Wired | Supported graphics resolutions: 704 x 480 | Supported graphics resolutions: 1920 x 1080 | Tilt angle range: -15 - 90° | Product colour: White

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903