



HIKVISION DS- 2CD1047G2H- LIUF/SL 2.8mm IP CAMERA



Modelis: DS-2CD1047G2H-LIUF/SL 2.8mm PL

Gamintojas: HIKVISION

EAN: 6936422114800

Prekės kodas: 367487

98.99€

Maximum memory card size: 512 GB | Number of lenses: 1 | Maximum aperture number: 1 | Video compression formats: H.265+ | Detect distance (wide): 63 m | Package height: 141 mm | Signal-to-Noise Ratio (SNR): 52 dB | Day/night mode: Yes | Password protection: Yes | Video compression formats: H.265 | Video compression formats: H.264 | Operating temperature (T-T): -30 - 60 °C | Maximum frame rate: 25 fps | Width: 69.1 mm | Video compression formats: M-JPEG | Package width: 150 mm | Minimum illumination: 0 lx | Recognize distance (wide): 12 m | PoE standard: IEEE 802.3af | Ethernet LAN (RJ-45) ports: 1 | Power over Ethernet (PoE): Yes | Wide Dynamic Range (WDR): 120 dB | Observe distance (wide): 25 m | Video compression formats: H.264+ | Bit rate: 32 Kbps - 8 Mbps | Built-in microphone: Yes | Number of cameras: 1 | Sustainability certificates: REACH | Lens viewing angle, diagonal: 114° | Sustainability certificates: WEEE | Heartbeat: Yes | Storage temperature (T-T): -30 - 60 °C | Package weight: 540 g | Height: 67.4 mm | Product colour: White | Tilt angle range: 0 - 90° | Pan range: 0 - 355° | Lens viewing angle, horizontal: 96° | Progressive scan: Yes | Lens viewing angle, vertical: 52° | International Protection (IP) code: IP67 | Mirror: Yes | Compatible memory cards:

MicroSD (TransFlash) | Compatible memory cards: MicroSDXC | Face detection: Yes | Maximum

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

resolution: 2560 x 1440 pixels | Compatible memory cards: MicroSDHC | Quality of Service (QoS) support: Yes | Package depth: 150 mm | Operating relative humidity (H-H): 0 - 95% | Housing material: Metal | Type: IP security camera | Night vision: Yes | Identify distance (wide): 6 m | DC output current: 0.6 A | Storage relative humidity (H-H): 0 - 95% | LED type: IR | Power management: DC 12 V | Weight: 320 g | Depth: 179 mm | Video motion detection: Yes | Client interoperability: ONVIF (Profile S / (Profile T / (Profile G), ISAPI, SDK | Number of users: 32 user(s) | Ethernet LAN: Yes | Sensor type: CMOS | Housing material: Plastic | Total megapixels: 4 MP | Ethernet LAN data rates: 10,100 Mbit/s | Region of Interest (ROI) encoding: Yes | Night vision distance: 30 m | Infra-red wavelength: 850 nm | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Camera shutter speed: 1/3 - 1/100000 s | Optical sensor size: 1/3" / 1/2.8" | Warnings: The product contains electronic components do not dispose of with the normal household waste. | Warnings: Avoid direct contact with water to prevent electrical damage. | Warnings: Ensure that the product is properly installed and protected against falling.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903