



**Hikvision DS-
2CD2123G2-
LIS2U(2.8mm)
Dome IP
security camera
Indoor &
outdoor 1920 x
1080 pixels
Ceiling/wall**

Modelis: DS-2CD2123G2-LIS2U(2.8mm)

Gamintojas: HIKVISION

EAN: 6942160462691

Prekės kodas: 367488

117.99€

Certification: CE-EMC: EN 55032:2015+A1:2020, EN 50130-4:2011+A1:2014, EN IEC 61000-3-2:2019+A1:2021, EN 61000-3-3:2013+A1:2019+A2:2021, RCM: AS/NZS CISPR 32: 2015, IC: ICES-003: Issue 7, KC: KN32: 2015, KN35: 2015 CB: IEC 62368-1: 2014+A11, CE-LVD: EN 62368-1: 2014/A11: 2017, BIS: IS 13252 (Part 1): 2010/IEC 60950-1: 2005, LOA: IEC/EN 60950-1 CE-RoHS: 2011/65/EU, WEEE: 2012/19/EU, Reach: Regulation (EC) No 1907/2006 IP67: IEC 60529-2013, IK10: IEC 62262:2002 | Bit rate range: 32 - 320 Kbit/s | Number of simultaneous live view channels: 6

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

channels | Lens viewing angle, vertical: 61° | Digest authentication: Yes | Sample rates: 8 - 48 kHz | Lens viewing angle, horizontal: 112° | Lens viewing angle, diagonal: 132° | LED type: IR/White | Mirror: Yes | Number of users: 32 user(s) | Number of sensors: 1 | Diameter: 12.2 cm | Back Light Compensation (BLC): Yes | Password reset via email: Yes | Heartbeat: Yes | Minimum illumination: 0 lx | Recognize distance: 8 m | Observe distance: 16 m | Web browser: Yes | Video motion detection: Yes | Alarm input channels: 1 | Progressive scan: Yes | User access level: Administrator, Operator, User | Frame rate: 30 fps | Fixed focal length: 2.8 mm | Alarm input/output: Yes | Identify distance: 4 m | Audio input channels: 1.0 channels | Alarm output channels: 1 | Placement supported: Indoor & outdoor | Noise reduction technology: 3D noise reduction | Noise reduction: Yes | Region of Interest (ROI) encoding: Yes | Live view: Yes | Audio codecs: G.711/G.722.1/G.726/MP2L2/PCM/MP3/AAC-LC | Languages support: Multi | Camera shutter speed: 1/3 - 1/100000 s | Total megapixels: 2 MP | Gain control type: Auto | Video compression formats: H.265+ | Video compression formats: H.264+ | Maximum aperture number: 1.6 | Pan range: 0 - 355° | Number of languages: 33 | Infrared (IR) cut-off filter: Yes | Video compression formats: H.265 | Sensor type: CMOS | Day/night mode: Yes | IP address filtering: Yes | Mounting type: Ceiling/wall | Power consumption (Power over Ethernet (PoE)): 8.5 W | Highlight Compensation (HLC): Yes | Optical sensor size: 25.4 / 2.7 mm (1 / 2.7") | Infra-red wavelength: 850 nm | Housing material: Aluminium | Dynamic range: 120 dB | Angle of rotation: 355° | Behavior analysis: Line crossing detection | DC output current: 0.6 A | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Video streaming: Yes | Active tampering alarm: Yes | Pixel counter: Yes | DC output voltage: 12 | Detect distance: 42 m | Number of lenses: 1 | Signal-to-Noise Ratio (SNR): 52 dB | Maximum memory card size: 512 GB | Password protection: Yes | Night vision: Yes | Video compression formats: H.264 | HTTPS encryption: Yes | Supported graphics resolutions: 640 x 360 | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 1280 x 720 (HD 720) | Operating relative humidity (H-H): 0 - 95% | Ethernet interface type: Fast Ethernet | Compatible memory cards: MicroSDHC | Compatible memory cards: MicroSD (TransFlash) | Compatible memory cards: MicroSDXC | Protection features: Vandal proof | Ethernet LAN: Yes | Power consumption (max): 7.2 W | Tilt angle range: 0 - 75° | Weight: 600 g | Number of cameras: 1 | International Protection (IP) code: IP67 | Audio output channels: 1.0 channels | Height: 97.6 mm | Package weight: 800 g | Wide Dynamic Range (WDR): Yes | Package depth: 150 mm | Product colour: White | Storage temperature (T-T): -30 - 60 °C | Audit log: Yes | Storage relative humidity (H-H): 0 - 95% | Security algorithms: TLS | Ethernet LAN (RJ-45) ports: 1 | Operating temperature (T-T): -30 - 60 °C | Package height: 141 mm | Night vision distance: 30 m | Type: IP security camera | Networking standards: IEEE 802.3af | Card reader integrated: Yes | IK code: IK10 | Protection features: Dust resistant | Maximum resolution:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

1920 x 1080 pixels | Reset button: Yes | Package width: 150 mm | Bit rate: 32 Kbps - 8 Mbps | Form factor: Dome | Wi-Fi: No | Connectivity technology: Wired | Protection features: Water resistant | Power source type: DC, PoE | Built-in microphone: Yes | Bluetooth: No | Number of Privacy masking areas: 8

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903