



Hikvision DS-2CD1027G0-L Bullet IP security camera Outdoor 1920 x 1080 pixels Ceiling/wall

Modelis: DS-2CD1027G0-L(2.8mm)

Gamintojas: HIKVISION

EAN: 6941264051374

Prekės kodas: 367489

61.99€

Certification: FCC (47 CFR 15, B) CE-EMC (EN 55032: 2015, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 50130-4: 2011 +A1: 2014) RCM (AS/NZS CISPR 32: 2015) IC (ICES-003: 6, 2016) KC (KN 32: 2015, KN 35: 2015) UL (UL 60950-1) CB (IEC 60950-1:2005 + Am 1:2009 + Am 2:2013) CE-LVD (EN 60950-1:2005 + Am 1:2009 + Am 2:2013) BIS (IS 13252(1):2010+A1:2013+A2:2015) CE-RoHS (2011/65/EU) WEEE (2012/19/EU) Reach ((EC) No 1907/2006) | Tilt angle range: 0 - 90° | Power consumption (max): 3.6 W | Weight: 420 g | Power source type: DC, PoE | Connectivity technology: Wired | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Width: 68.4 mm | Package weight: 510 g | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 640 x 480 (VGA) | Product colour: Black | Wi-Fi: No | Quality of Service (QoS) support: Yes | Ethernet LAN

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

(RJ-45) ports: 1 | International Protection (IP) code: IP67 | Length: 161.1 mm | Storage relative humidity (H-H): 0 - 95% | Security algorithms: TLS | Operating temperature (T-T): -30 - 60 °C | Maximum resolution: 1920 x 1080 pixels | Package width: 172 mm | Package depth: 104 mm | Type: IP security camera | Form factor: Bullet | Supported graphics resolutions: 320 x 240 | Supported graphics resolutions: 640 x 360 | Storage temperature (T-T): -30 - 60 °C | Product colour: White | Networking standards: IEEE 802.3af | Supported graphics resolutions: 1280 x 960 | Bluetooth: No | Operating relative humidity (H-H): 0 - 95% | Web-based management: Yes | Security algorithms: HTTPS | Package height: 80 mm | Lens viewing angle, vertical: 56° | Placement supported: Outdoor | Maximum aperture number: 1 | Video compression formats: H.265+ | Night vision: Yes | Ethernet interface type: Fast Ethernet | DC output voltage: 12 | Lens viewing angle, horizontal: 107° | Noise reduction: Yes | Heartbeat: Yes | Camera tilt control: Yes | Pan range: 0 - 360° | Housing material: Metal | Number of users: 32 user(s) | Camera shutter speed: 1/3 - 1/100000 s | Depth: 65.2 mm | IP address filtering: Yes | Lens viewing angle, diagonal: 127° | Total megapixels: 2 MP | Camera pan control: Yes | Sensor type: CMOS | Video compression formats: H.265 | Ethernet LAN: Yes | Angle of rotation: 360° | Digital Wide Dynamic Range (DWDR): Yes | Video compression formats: M-JPEG | Noise reduction technology: 3D noise reduction | Frame rate: 30 fps | Fixed focal length: 2.8 mm | Supported network protocols: TCP/IP, ICMP, HTTP, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IGMP, QoS, IPv6, UDP, Bonjour, SSL/TLS | Closest focusing distance: 1.7 m | DC output current: 0.3 A | Progressive scan: Yes | Back Light Compensation (BLC): Yes | Minimum illumination: 0.001 lx | Number of cameras: 1 | Built-in HDD: No | Video compression formats: H.264+ | Bit rate: 32 Kbps - 8 Mbps | Image quality adjustment: Contrast | Number of languages: 1 | Region of Interest (ROI) encoding: Yes | Languages support: English | Night vision distance: 30 m | Optical sensor size: 25.4 / 2.8 mm (1 / 2.8") | Image quality adjustment: Sharpness | Video motion detection: Yes | Privacy masking: Yes | Password protection: Yes | Day/night mode: Yes | Image quality adjustment: Brightness | Number of sensors: 1 | Video streaming: Yes | Mounting type: Ceiling/wall | Wide Dynamic Range (WDR): Yes | Mirror: Yes | HTTPS encryption: Yes | Video compression formats: H.264 | Anti-flicker: Yes | Image quality adjustment: Saturation | Highlight Compensation (HLC): Yes | Power consumption (Power over Ethernet (PoE)): 4.5 W | Number of lenses: 1

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903