



Ezviz HB8 IP camera + solar panel



Modelis: HB8

Gamintojas: EZVIZ

EAN: 6941545639260

Prekės kodas: 367703

95.99€

Reset button: Yes | Form factor: Dome | Type: IP security camera | Power source type: DC, PoE | Maximum resolution: 2560 x 1440 pixels | Built-in HDD: No | Connectivity technology: Wired | Storage relative humidity (H-H): 0 - 95% | Wi-Fi: No | Ethernet interface type: 10 Megabit Ethernet | Ethernet interface type: 100 Megabit Ethernet | Ethernet interface type: Fast Ethernet | Ethernet interface type: 1 Gigabit Ethernet | Ethernet interface type: 5 Gigabit Ethernet | Day/night mode: Yes | Power consumption (max): 5 W | Ethernet interface type: 25 Gigabit Ethernet | Operating relative humidity (H-H): 0 - 95% | Ethernet interface type: 100 Gigabit Ethernet | Ethernet interface type: 10 Gigabit | Ethernet interface type: 10 Gigabit Ethernet, Gigabit Ethernet | Ethernet interface type: Gigabit Ethernet | Ethernet interface type: 10 Gigabit Ethernet, Fast Ethernet, Gigabit Ethernet | Ethernet interface type: 2x 1 Gigabit Ethernet | Placement supported: Outdoor | Ethernet interface type: 10 Gigabit Ethernet | Ethernet interface type: 2.5 Gigabit Ethernet | Ethernet interface type: 16 Gigabit Ethernet | Ethernet interface type: 1000 Gigabit Ethernet | Live view: Yes | Camera shutter speed: 1/3 - 1/100000 s | Product colour: White | Operating temperature (T-T): -10 - 50 °C | Ethernet LAN: Yes | Audio formats supported: PCM | Number of cameras: 1 | Ethernet interface type: 40 Gigabit Ethernet | Ethernet interface type: Fast Ethernet, Gigabit Ethernet | Ethernet interface type:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

1.25 Gigabit Ethernet | Minimum illumination: 0 lx | Ethernet LAN (RJ-45) ports: 1 | Mounting type: Ceiling/Pole | Storage temperature (T-T): -10 - 50 °C | Sustainability compliance: Yes | User access level: Administrator, Operator, User | Audio formats supported: MP2L2 | Audio formats supported: G.722.1 | Sensor type: CMOS | Audio formats supported: G.711 μ -law | Audio formats supported: G.726 | Audio formats supported: AAC-LC | Audio formats supported: G.711 A-law | Compliance certificates: UL | Compliance certificates: CB | Compliance certificates: BIS | Compliance certificates: KC | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Industry Canada (IC)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903