AG Neovo QM-4303 Flat panel monitor Digital Signage 43 500 cd/m 4K Ultra HD Black

Modelis: QM-4303

Gamintojas: AG NEOVO

EAN: 4710739598605

Prekės kodas: 367724

528.99€

Certification: CE LVD WEEE RoHS REACH EAC UKCA | Remote (IR) output: 1 | Compliance certificates: REACH | Built-in speaker(s): Yes | USB port: Yes | Number of built-in speakers: 2 | Display depth: 70 mm | Display brightness: 500 cd/m² | Placement supported: Indoor | Display width: 971 mm | Surface hardness: 3H | Compliance certificates: WEEE | Compliance certificates: RoHS | Compliance certificates: CE | Anti-glare screen: Yes | Operating hours (hours/days): 24/7 | USB playback: Yes | Mounting type: Wall | USB version: 2.0 | Energy efficiency scale: A to G | Power consumption (standby): 0.5 W | Remote control included: Yes | Contrast ratio (typical): 4000:1 | RMS rated power: 2 x 10 W | Display weight: 8 kg | VGA (D-Sub) input ports: 1 | Orientation: Horizontal/Vertical | Panel type: VA | Display height: 559 mm | Haze rate: 25% | Purpose: Universal | PC Audio in: Yes | USB ports quantity: 1 | Built-in processor: No | Computer system: No | Energy consumption (SDR) per 1000 hours: 99 kWh | Energy efficiency class (SDR): G | Compliance certificates: Low Voltage

Directive (LVD) | Warnings: The product should be disposed of by specialist disposal facilities for electronic equipment. | Hazard pictogram(s): GHS09: Environmental hazard | Warnings: Do not open the appliance housing, risk of electric shock. | Warnings: The monitor contains substances hazardous to health, including mercury avoid contact with damaged parts. | Hazard pictogram(s): GHS07: Harmful | Display resolution: 3840 x 2160 pixels | AC input frequency: 50 - 60 Hz | Power consumption (off): 0.3 W | Package weight: 11.5 kg | Storage relative humidity (H-H): 10 - 90% | Cable lock slot type: Kensington | Display diagonal: 109.2 cm (43") | Horizontal scan range: 15 - 135 kHz | Viewing angle, vertical: 178° | HD type: 4K Ultra HD | Viewing angle, horizontal: 178° | Product colour: Black | Storage temperature (T-T): 20 - 80 °C | Operating relative humidity (H-H): -20 - 60% | Operating temperature (T-T): 0 - 40 °C | Package width: 1075 mm | Pixel pitch: 0.245 x 0.245 mm | Response time: 5 ms | Ethernet LAN (RJ-45) ports: 1 | Display number of colours: 1,07G | Native aspect ratio: 16:9 | AC input voltage: 100 - 240 V | Ethernet LAN: Yes | HDMI version: 2.0 | RS-232 interface: Yes | Product design: Digital signage flat panel | HDMI ports quantity: 2 | Touchscreen: No | Package height: 652 mm | Vertical scan range: 24 - 85 Hz | Package depth: 144 mm | Cables included: HDMI | Batteries included: Yes | Cables included: AC | DVI port: No | Wi-Fi: No | VESA mounting: Yes | Panel mounting interface: 300 x 300 mm | Power consumption (typical): 102 W