AG Neovo QM-5503 Flat panel monitor Digital Signage 55 500 cd/m 4K Ultra HD Black

Modelis: QM-5503

Gamintojas: AG NEOVO

EAN: 4710739598612

Prekės kodas: 367725

680.99€

Certification: CE LVD WEEE RoHS REACH EAC UKCA | Anti-glare screen: Yes | Surface hardness: 3H | Remote (IR) output: 1 | Warnings: Do not open the appliance housing, risk of electric shock. | Compliance certificates: WEEE | Hazard pictogram(s): GHS07: Harmful | Compliance certificates: REACH | Panel mounting interface: 300 x 300 mm | Compliance certificates: Low Voltage Directive (LVD) | Compliance certificates: RoHS | Compliance certificates: CE | Built-in speaker(s): Yes | Built-in processor: No | Display depth: 70 mm | USB port: Yes | Hazard pictogram(s): GHS09: Environmental hazard | Warnings: The monitor contains substances hazardous to health, including mercury avoid contact with damaged parts. | Batteries included: Yes | Warnings: The product should be disposed of by specialist disposal facilities for electronic equipment. | Placement supported: Indoor | Haze rate: 25% | Energy consumption (SDR) per 1000 hours: 134 kWh | Purpose: Universal | Touchscreen: No | Number of built-in speakers: 2 | Operating hours (hours/days): 24/7 | USB playback: Yes | USB ports

quantity: 1 | Mounting type: Wall | Energy efficiency scale: A to G | Display brightness: 500 cd/m² | Power consumption (standby): 0.5 W | HDMI ports quantity: 2 | Remote control included: Yes | Display weight: 13 kg | Wi-Fi: No | VESA mounting: Yes | Energy efficiency class (SDR): G | Display width: 1238.4 mm | Contrast ratio (typical): 4000:1 | RMS rated power: 2 x 10 W | DVI port: No | VGA (D-Sub) input ports: 1 | USB version: 2.0 | RS-232 interface: Yes | PC Audio in: Yes | Panel type: VA | Display height: 709.2 mm | Ethernet LAN: Yes | HDMI version: 2.0 | Orientation: Horizontal/Vertical | Computer system: No | Product design: Digital signage flat panel | Pixel pitch: 0.245 x 0.245 mm | Operating relative humidity (H-H): -20 - 60% | Display diagonal: 139.7 cm (55") | Package width: 1390 mm | AC input frequency: 50 - 60 Hz | Display resolution: 3840 x 2160 pixels | Ethernet LAN (RJ-45) ports: 1 | Storage relative humidity (H-H): 10 - 90% | Vertical scan range: 24 - 85 Hz | Display number of colours: 1,07G | Cables included: HDMI | Cable lock slot type: Kensington | AC input voltage: 100 - 240 V | Cables included: AC | Package weight: 17.6 kg | Native aspect ratio: 16:9 | Response time: 5 ms | Product colour: Black | HD type: 4K Ultra HD | Power consumption (off): 0.3 W | Package depth: 144 mm | Storage temperature (T-T): 20 - 80 °C | Operating temperature (T-T): 0 - 40 °C | Package height: 830 mm | Viewing angle, horizontal: 178° | Power consumption (typical): 102 W | Horizontal scan range: 15 - 135 kHz | Viewing angle, vertical: 178°