



Hikvision DS- 2CD2726G2-IZS Dome IP security camera Outdoor 1920 x 1080 pixels Ceiling/wall

Modelis: DS-2CD2726G2-IZS(2.8-12mm)©

Gamintojas: HIKVISION

EAN: 6931847120238

Prekės kodas: 367728

153.98€

Certification: FCC (47 CFR 15, B) CE-EMC (EN 55032: 2015, EN 61000-3-2: 2014, EN 61000-3-3: 2013, EN 50130-4: 2011 +A1: 2014) RCM (AS/NZS CISPR 32: 2015) IC (ICES-003: 6, 2016) KC (KN 32: 2015, KN 35: 2015) UL (UL 60950-1) CB (IEC 60950-1:2005 + Am 1:2009 + Am 2:2013) CE-LVD (EN 60950-1:2005 + Am 1:2009 + Am 2:2013) BIS (IS 13252(1):2010+A1:2013+A2:2015) LOA (IEC/EN 60950-1) CE-ROHS (2011/65/EU) WEEE (2012/19/EU) REACH ((EC) No 1907/2006) | Ethernet interface type: Fast Ethernet | Operating relative humidity (H-H): 0 - 95% | Power source type: DC, PoE | Night vision distance: 40 m | Frame rate: 30 fps | IK code: IK10 | Camera shutter speed: 1/3 - 1/100000 s | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 640 x 480 (VGA) | Total megapixels: 2 MP | Supported graphics resolutions: 640 x 360 | Networking

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

standards: IEEE 802.3af | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Pan range: 0 - 355° | Diameter: 15.3 cm | International Protection (IP) code: IP66 | Number of cameras: 1 | Highlight Compensation (HLC): Yes | Quality of Service (QoS) support: Yes | Audio formats supported: MP3 | Height: 133.1 mm | Package weight: 1.72 kg | Wide Dynamic Range (WDR): Yes | Compatible memory cards: MicroSD (TransFlash) | Supported network protocols: TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, NTP, UPnP, SMTP, IGMP, 802.1X, QoS, IPv6, UDP, Bonjour, SSL/TLS | Tilt angle range: 0 - 75° | Ethernet LAN: Yes | Angle of rotation: 355° | Bluetooth: No | Weight: 840 g | Power consumption (max): 10.5 W | Operating temperature (T-T): -30 - 60 °C | Wi-Fi: No | Ethernet LAN (RJ-45) ports: 1 | Back Light Compensation (BLC): Yes | Package width: 244 mm | LED type: IR | Form factor: Dome | Bit rate: 32 Kbps - 8 Mbps | Connectivity technology: Wired | Storage temperature (T-T): -30 - 60 °C | Minimum illumination: 0 lx | Product colour: White | Package depth: 174 mm | Maximum resolution: 1920 x 1080 pixels | Storage relative humidity (H-H): 0 - 95% | Type: IP security camera | Package height: 173 mm | Housing material: Metal | Networking standards: IEEE 802.1x | Card reader integrated: Yes | IP address filtering: Yes | Languages support: Dutch | Languages support: Czech | Languages support: Spanish | Languages support: Hungarian | Camera tilt control: Yes | Maximum memory card size: 256 GB | Video motion detection: Yes | Privacy masking: Yes | Voice codecs: G.711ulaw | Number of sensors: 1 | Voice codecs: AAC | Number of languages: 33 | Lens viewing angle, vertical: 58° | Detect distance (wide): 44.1 m | Maximum aperture number: 1.4 | Built-in HDD: No | Progressive scan: Yes | Voice codecs: G.726 | Observe distance (wide): 17.5 m | Voice codecs: G.722.1 | Video streaming: Yes | Mounting type: Ceiling/wall | Behavior analysis: Intrusion detection, Line crossing detection, Region entrance detection, Region exiting detection | DC output voltage: 12 | Noise reduction: Yes | Voice codecs: MP2L2 | Languages support: French | Languages support: Vietnamese | Noise reduction technology: 3D noise reduction | Observe distance (tele): 52 m | Anti-flicker: Yes | Infrared (IR) cut-off filter: Yes | Languages support: Greek | Languages support: Estonian | Languages support: Portuguese | Languages support: Slovenian | Placement supported: Outdoor | Number of lenses: 1 | Languages support: Lithuanian | Languages support: Turkish | Languages support: Thai | Region of Interest (ROI) encoding: Yes | Languages support: English | Sensor type: CMOS | Lens viewing angle, diagonal: 138° | Languages support: Slovak | Number of users: 32 user(s) | Power consumption (Power over Ethernet (PoE)): 12.5 W | Identify distance (wide): 4.4 m | Voice codecs: G.711alaw | Optical sensor size: 25.4 / 2.8 mm (1 / 2.8") | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Languages support: Bulgarian | Languages support: Swedish | DC output current: 0.88 A | Languages support: German | Languages support: Polish | Languages support: Japanese | Languages support: Russian | Languages support: Norwegian | Recognize distance (tele): 26.2 m | Languages support: Danish | Languages

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shoppro.lt | info@shoppro.lt | +370 693 39903

support: Ukrainian | Languages support: LAT | Identify distance (tele): 13.1 m | Languages support: Finnish | Languages support: Italian | Languages support: Traditional Chinese | Detect distance (tele): 131 m | Night vision: Yes | Languages support: Korean | Languages support: Romanian | Languages support: SER | Infra-red wavelength: 850 nm | Password protection: Yes | Lens viewing angle, horizontal: 113° | Focal length range: 2.8 - 12 mm | Mirror: Yes | Image quality adjustment: Brightness | Intelligent Video Surveillance (IVS) system features: Scene change | Image quality adjustment: Sharpness | Sample rate: 48 kHz | Day/night mode: Yes | Video compression formats: H.265+ | Heartbeat: Yes | Image quality adjustment: Contrast | Camera pan control: Yes | Recognize distance (wide): 8.8 m | HTTPS encryption: Yes | Image quality adjustment: Saturation | Video compression formats: M-JPEG | Video compression formats: H.264+ | Video compression formats: H.264 | Video compression formats: H.265

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903