



# Hikvision Value Series 8 MP Smart Hybrid Light Fixed Turret Network Camera



Modelis: DS-2CD1383G2-LIUF/SL 2.8mm PL

Gamintojas: HIKVISION

EAN: 6936422114657

Prekės kodas: 367731

## 110.99€

Audit log: Yes | Compliance certificates: BIS | Number of Privacy masking areas: 4 | Lens viewing angle, horizontal: 113° | Mounting type: Ceiling/Wall/Pole | Heartbeat: Yes | Built-in speaker(s): Yes | Image quality adjustment: Saturation | Image quality adjustment: Brightness | Languages support: Ukrainian | Languages support: English | Number of simultaneous live view channels: 6 channels | Infra-red wavelength: 850 nm | Lens viewing angle, diagonal: 134° | Password protection: Yes | Power consumption (Power over Ethernet (PoE)): 9.5 W | Mirror: Yes | Digital watermark: Yes | Video compression formats: M-JPEG | Video compression formats: H.265+ | Video compression formats: H.265 | DC output voltage: 12 | Day/night mode: Yes | Active tampering alarm: Yes | DC output current: 0.66 A | Number of lenses: 1 | Password reset via email: Yes | Video motion detection: Yes | Night vision: Yes | User access level: Administrator, Operator, User | Video compression formats: H.264+ | Digest authentication: Yes | Image quality adjustment: Contrast | Image quality adjustment:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Sharpness | Sensor type: CMOS | Video compression formats: H.264 | Number of users: 32 user(s) | Lens viewing angle, vertical: 62° | Dynamic range: 120 dB | Identify distance: 7 m | Placement supported: Indoor & outdoor | Maximum resolution: 3840 x 2160 pixels | Built-in microphone: Yes | Power source type: DC, PoE | Reset button: Yes | Package height: 141 mm | Package depth: 150 mm | Built-in light: Yes | Type: IP security camera | Card reader integrated: No | Product colour: White | Connectivity technology: Wired | Tilt angle range: 0 - 75° | Number of languages: 2 | Weight: 385 g | Storage relative humidity (H-H): 0 - 95% | Storage temperature (T-T): -30 - 60 °C | Bluetooth: No | Infrared (IR) cut-off filter: Yes | Networking standards: IEEE 802.3af | Operating relative humidity (H-H): 0 - 95% | Power consumption (max): 8 W | Operating temperature (T-T): -30 - 60 °C | Ethernet LAN (RJ-45) ports: 1 | Audio system: 2-way | Camera shutter speed: 1/3 - 1/100000 s | Supported graphics resolutions: 3840 x 2160 | Supported graphics resolutions: 2688 x 1520 | Sample rates: 8 - 16 kHz | Bit rate range: 16 - 160 Kbit/s | Compatible memory cards: MicroSD (TransFlash) | Optical sensor size: 25.4 / 2.7 mm (1 / 2.7") | Ethernet interface type: Fast Ethernet | Package weight: 586 g | Form factor: Turret | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 3200 x 1800 | Maximum aperture number: 2 | International Protection (IP) code: IP67 | Ethernet LAN: Yes | Angle of rotation: 360° | Back Light Compensation (BLC): Yes | Compliance certificates: CB | Compliance certificates: RoHS | Compliance certificates: CE | Diameter: 11 cm | Compliance certificates: WEEE | Supported graphics resolutions: 1280 x 720 (HD 720) | Observe distance: 31 m | Housing material: Metal | Highlight Compensation (HLC): Yes | Audio formats supported: G.722.1 | Audio formats supported: MP2L2 | Total megapixels: 8 MP | Region of Interest (ROI) encoding: Yes | Wi-Fi: No | Bit rate: 32 Kbps - 16 Mbps | Protection features: Water resistant | Fixed focal length: 2.8 mm | Supported network protocols: TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, NTP, IGMP, IPv6, UDP, QoS, FTP, SMTP, UPnP | Audio formats supported: AAC-LC | Noise reduction: Yes | Protection features: Dust resistant | Package width: 150 mm | Wide Dynamic Range (WDR): Yes | Maximum memory card size: 512 GB | Number of cameras: 1 | Compliance certificates: RCM | Compliance certificates: Electromagnetic Compatibility (EMC) | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Night vision distance: 30 m | Progressive scan: Yes | Audio formats supported: G.726 | Audio formats supported: G.711 | Compliance certificates: Low Voltage Directive (LVD) | Audio formats supported: PCM | Detect distance: 79 m | Compliance certificates: UL | Supported graphics resolutions: 640 x 360 | Lens mount interface: M12 | Noise reduction technology: 3D noise reduction | Height: 102.7 mm | Minimum illumination: 0 lx | Signal-to-Noise Ratio (SNR): 52 dB | Compliance certificates: REACH | Compatible memory cards: MicroSDHC | Housing material: Plastic | Compatible memory cards:

**MicroSDXC | LED type: IR | Recognize distance: 15 m | Built-in HDD: No | Pan range: 0 - 360°**

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903