



# HIKVISION DS- 2CD1061G2-LIU 2.8mm IP CAMERA



Modelis: DS-2CD1061G2-LIU 2.8mm PL

Gamintojas: HIKVISION

EAN: 6936422131029

Prekės kodas: 367732

## 70.99€

Number of Privacy masking areas: 4 | Audit log: Yes | Width: 66 mm | Supported graphics resolutions: 3200 x 1800 | Pan range: 0 - 360° | Length: 170.8 mm | Number of cameras: 1 | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Bit rate range: 16 - 160 Kbit/s | Built-in light: Yes | Package weight: 481 g | Height: 69.1 mm | Built-in microphone: Yes | Client interoperability: iVMS-4200, Hik-Connect | Supported graphics resolutions: 640 x 360 | Number of languages: 1 | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 2688 x 1520 | Power source type: DC, PoE | Storage temperature (T-T): -30 - 60 °C | Signal-to-Noise Ratio (SNR): 52 dB | Package height: 118 mm | Weight: 285 g | Wi-Fi: No | Bluetooth: No | Package depth: 121 mm | Supported graphics resolutions: 640 x 480 (VGA) | Protection features: Waterproof | Minimum illumination: 0 lx | Maximum resolution: 3200 x 1800 pixels | Operating temperature (T-T): -30 - 60 °C | Package width: 216 mm | Progressive scan: Yes | Wide Dynamic Range (WDR): Yes | Ethernet LAN (RJ-45) ports: 1 | Back Light Compensation (BLC): Yes | International Protection (IP) code: IP67 | Housing material: Metal | Web-based management: Yes |

Connectivity technology: Wired | Storage relative humidity (H-H): 0 - 95% | Supported graphics

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

resolutions: 1920 x 1080 (HD 1080) | Form factor: Bullet | Bit rate: 32 Kbps - 16 Mbps | Digest authentication: Yes | Power consumption (max): 5 W | Operating relative humidity (H-H): 0 - 95% | Sample rates: 8 - 16 kHz | Ethernet interface type: Fast Ethernet | Fixed focus: Yes | Total megapixels: 6 MP | Highlight Compensation (HLC): Yes | Type: IP security camera | Product colour: White | Audio formats supported: G.726 | Tilt angle range: 0 - 90° | Audio formats supported: G.711 | Ethernet LAN: Yes | Angle of rotation: 360° | Audio formats supported: PCM | Supported network protocols: TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, NTP, IGMP, IPv6, UDP, QoS, FTP, SMTP | Audio formats supported: MP2L2 | Night vision distance: 30 m | Optical sensor size: 25.4 / 2.4 mm (1 / 2.4") | Housing material: Plastic | Built-in HDD: No | Camera shutter speed: 1 - 1/100000 s | Privacy protection: Yes | Audio formats supported: G.722.1 | Audio formats supported: AAC-LC | Password protection: Yes | User access level: Administrator, Operator, User | Identify distance: 7 m | Number of lenses: 1 | Digital watermark: Yes | Fixed focal length: 2.8 mm | Dynamic range: 120 dB | Detect distance: 76 m | Region of Interest (ROI) encoding: Yes | Live view: Yes | Number of simultaneous live view channels: 6 channels | Infra-red wavelength: 850 nm | Languages support: Polish | DC output current: 0.41 A | Recognize distance: 15 m | Video compression formats: H.264+ | Video compression formats: H.264 | Mirror: Yes | Night vision: Yes | Compliance certificates: CB | Image quality adjustment: Brightness | Compliance certificates: WEEE | Compliance certificates: RCM | Video compression formats: H.265+ | Power consumption (Power over Ethernet (PoE)): 6.5 W | Lens viewing angle, horizontal: 105° | Mounting type: Ceiling/wall | Video motion detection: Yes | Privacy masking: Yes | DC output voltage: 12 | Number of users: 32 user(s) | Placement supported: Indoor & outdoor | Compliance certificates: Low Voltage Directive (LVD) | Lens viewing angle, vertical: 55° | Compliance certificates: RoHS | Compliance certificates: CE | Sensor type: CMOS | Maximum aperture number: 1.6 | Video compression formats: M-JPEG | Observe distance: 30 m | Video compression formats: H.265 | Lens viewing angle, diagonal: 127° | Number of sensors: 1 | Image quality adjustment: Saturation | Heartbeat: Yes | Image quality adjustment: Contrast | Image quality adjustment: White balance | Day/night mode: Yes | Compliance certificates: REACH | Image quality adjustment: Sharpness | Password reset via email: Yes | Infrared (IR) cut-off filter: Yes | Video streaming: Yes | Sustainability compliance: Yes

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903