



XPG CORE REACTOR II 1000W Power Supply



Modelis: 75261209

Gamintojas: XPG

EAN: 4711085942395

Prekės kodas: 367741

136.98€

Compliance certificates: cTUVus | Compliance certificates: Norma Oficial Mexicana (NOM) |
Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: BSMI |
Compliance certificates: CB | Compliance certificates: EAC | Compliance certificates: RCM |
Compliance certificates: UKCA | Compliance certificates: CE | Compliance certificates: China
Compulsory Certification (CCC) | ATX power connector (12+4 pin): Yes | Warnings: The product is not
suitable for disposal with municipal waste - dispose of in accordance with local regulations. |
Warnings: Do not open the case - risk of electric shock. | Warnings: Avoid contact of the product with
water or other liquids. | Purpose: PC | Depth: 150 mm | Number of fans: 1 fan(s) | EPS power
connector (8-pin): Yes | Width: 160 mm | AC input voltage: 100 - 240 V | Package weight: 3.43 kg |
80 PLUS certification: 80 PLUS Gold | Height: 86 mm | Package width: 210 mm | Power protection
features: Under voltage | Power protection features: Over current | Power protection features: Surge
& inrush protection (SIP) | Power protection features: Short circuit | Power protection features: Over
voltage | Fan diameter: 13.5 cm | Input current: 13 A | ATX Power connector (24-pin): Yes | Weight:
1.77 kg | Power protection features: Over power | Cooling type: Active | Power protection features:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be
išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

išsijyngant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Overheating | Peripheral (Molex) power connectors (4-pin): 3 | Product colour: Black | Package depth: 338 mm | Package height: 157 mm | AC input frequency: 50/60 Hz | ATX version: 3.0 | Max output current (-12V): 0.3 A | Motherboard power connector: 24-pin ATX | Power supply unit (PSU) form factor: ATX | EPS version: 2.92 | Max output current (+3.3V): 22 A | Cabling type: Fully-Modular | Total power: 1000 W | Max output current (+5V): 22 A | Bearing technology: FDB | Mean time between failures (MTBF): 100000 h | Max output current (+12V): 83.5 A | PCI Express power connectors (6+2 pin): 8 | Power factor: 0.99 | Max output current (+5Vsb): 3 A | Number of SATA power connectors: 9

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903