



Cudy PE25 network card Internal Ethernet



Modelis: PE25

Gamintojas: CUDY

EAN: 6971690791483

Prekės kodas: 368114

15.98€

Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows 10 | Windows operating systems supported: Windows 7 | Windows operating systems supported: Windows 8 | Component for: PC/Server | Operating temperature (T-T): -10 - 60 °C | Ethernet LAN (RJ-45) ports: 1 | Package type: Box | Copper ethernet cabling technology: 1000BASE-TX | Copper ethernet cabling technology: 10BASE-T | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Server operating systems supported: Windows Server 2012 | Networking standards: IEEE 802.3bz | Storage relative humidity (H-H): 5 - 90% | Server operating systems supported: Windows Server 2008 | Wake-on-LAN ready: Yes | Networking standards: IEEE 802.3az | Networking standards: IEEE 802.3u | Connectivity technology: Wired | Ethernet LAN data rates: 1000 Mbit/s | Quick installation guide: Yes | Ethernet LAN data rates: 100 | Ethernet LAN data rates: 2500 | Ethernet LAN: Yes | Ethernet interface type: Gigabit Ethernet | Width: 71.5 mm | Ethernet LAN data rates: 10 | Operating relative humidity (H-H): 10 - 90% | Ethernet interface type: Fast Ethernet | Interface: Ethernet | Ethernet interface type: 2.5 Gigabit Ethernet | Internal: Yes | Depth: 50 mm | Storage temperature (T-T): -20 - 70 °C | Cabling technology: 10/100/1000BaseT(X) | Height: 1.6 mm |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

LED indicators: Link | LAN controller: Realtek RTL8125 | LED indicators: Activity | LED indicators: Speed | Host interface: PCI Express | Mean time between failures (MTBF): 376212 h | Resource CD: Yes | Jumbo frames support: Yes | PCI Card form factor: Full-height (low-profile) | Mounting brackets included: Yes | Full duplex: Yes | Flow control support: Yes | Low-profile bracket: Yes | Auto MDIX IEEE: Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903