



TP-Link Omada 16-Port Gigabit Smart Switch with 2 SFP Slots



Modelis: TL-SG2218

Gamintojas: TP-LINK

EAN: 6935364006419

Prekės kodas: 368510

143.99€

Certification: CE, FCC, RoHS | LED indicators: Yes | Power source: AC | Rate limiting: Yes | Loop protection: Yes | Heat dissipation: 41.97 BTU/h | Store-and-forward: Yes | Access Control List (ACL): Yes | AC input voltage: 100 - 240 V | Link aggregation: Yes | Jumbo frames support: Yes | Operating temperature (T-T): 0 - 40 °C | Broadcast storm control: Yes | Switch type: Managed | Number of IP interfaces: 16 | Rack mounting: Yes | ARP inspection: Yes | Power over Ethernet (PoE): No | Width: 440 mm | Height: 44 mm | Cables included: AC | SFP module slots quantity: 2 | Networking standards: IEEE 802.3ab | Web-based management: Yes | Networking standards: IEEE 802.3z | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.3u | MIB support: Yes | GARP VLAN Registration Protocol (GVRP): Yes | VLAN support: Yes | Number of static routes: 32 | MAC address table: 8000 entries | Networking standards: IEEE 802.3i | Management protocols: SNMPv1/v2c/v3, SNTP | Basic switching RJ-45 Ethernet ports quantity: 16 | Cloud-managed: Yes | Virtual LAN features: Voice VLAN | Virtual LAN features: Private VLAN | Multicast support: Yes | Ethernet LAN data rates: 10,100,1000 Mbit/s | Fanless: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Virtual LAN features: Port-based VLAN | Depth: 180 mm |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Virtual LAN features: Tagged VLAN | Packet buffer memory: 4.1 MB | Port mirroring: Yes | Cables included: LAN (RJ-45) | IGMP snooping: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Virtual LAN features: Protocol-based VLAN | Product colour: Black | Form factor: 1U | Forwarding rate: 26.8 Mpps | Switch layer: L2/L2+ | System event log: Yes | DHCP features: DHCP server | SSH/SSL support: Yes | DHCP features: DHCPv6 client | Switching capacity: 36 Gbit/s | DHCP features: DHCPv6 snooping | DHCP features: DHCP client | DHCP features: DHCP relay | DHCP features: DHCP snooping | BPDU filtering/protection: Yes | Gigabit Ethernet (copper) ports quantity: 16 | Power consumption (max): 12.3 W | Multicast Listener Discovery (MLD) snooping: Y | Quick start guide: Yes | Spanning tree protocol: Yes | Jumbo frames: 9000 | Power supply included: Yes | AC input frequency: 50/60 Hz | Static route: Yes | Operating relative humidity (H-H): 10 - 90% | 10G support: No | Number of VLANs: 4000 | Flow control support: Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903