



**Optoma X309ST
data projector
Desktop
projector 3700
ANSI lumens
DLP XGA
(1024x768) 3D
White**

Modelis: E9PD7DQ01EZ1

Gamintojas: OPTOMA

EAN: 5055387664975

Prekės kodas: 368600

466.00€

On Screen Display (OSD) languages: Vietnamese | On Screen Display (OSD) languages: Polish | On Screen Display (OSD) languages: Swedish | On Screen Display (OSD) languages: Hungarian | On Screen Display (OSD) languages: Japanese | On Screen Display (OSD) languages: Russian | On Screen Display (OSD) languages: Czech | On Screen Display (OSD) languages: Greek | On Screen Display (OSD) languages: Traditional Chinese | On Screen Display (OSD) languages: French | On Screen Display (OSD) languages: Romanian | On Screen Display (OSD) languages: Simplified Chinese | On Screen Display (OSD) languages: Danish | On Screen Display (OSD) languages: Indonesian | On Screen Display (OSD) languages: German | On Screen Display (OSD) languages: Italian | On Screen

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Display (OSD) languages: Dutch | On Screen Display (OSD) languages: English | On Screen Display (OSD) languages: Norwegian | On Screen Display (OSD) languages: Turkish | On Screen Display (OSD) languages: Spanish | RMS rated power: 10 W | HDMI connector type: Full-size | Remote control included: Yes | Power consumption (standby): 0.5 W | Contrast ratio (typical): 25000:1 | AC (power) in: Yes | Projector brightness: 3700 ANSI lumens | On Screen Display (OSD) languages: Arabic | On Screen Display (OSD) languages: Portuguese | On Screen Display (OSD) languages: Finnish | On Screen Display (OSD) languages: Farsi | Supported aspect ratios: 4:3 | Market positioning: Presentation | Supported aspect ratios: 16:9 | Keystone correction, vertical: -40 - 40° | Password protection: Yes | Lamps quantity: 1 lamp(s) | Supported 3D formats: Top and bottom | Supported 3D formats: Frame packing | Lamp power: 203 W | Analog signal format system: SECAM 4.25/4.4 | Fixed focal length: 7.15 mm | Supported 3D formats: Side by side | Analog signal format system: SECAM L | Projector native resolution: XGA (1024x768) | Analog signal format system: PAL 4.43 | Serial interface type: RS-232 | Projection distance: 0.4 - 3.1 m | Service life of light source (economic mode): 10000 h | Analog signal format system: SECAM K1 | Built-in speaker(s): Yes | Number of OSD languages: 25 | Composite video in: 1 | Offset: 115% | Screen size compatibility: 810.3 - 6281.4 mm (31.9 - 247.3") | PC in (D-Sub): Yes | Throw ratio: 0.617:1 | PC Audio out: Yes | Number of built-in speakers: 1 | Analog signal format system: NTSC J | PC Audio in: Yes | Projection technology: DLP | Service life of light source: 6000 h | Smart TV: No | Uniformity: 75% | Ceiling mounting supported: Y | Light source type: Lamp | Warnings: Avoid placing the projector in high humidity areas to prevent damage to the unit. | Warnings: Be careful when replacing the projector lamp as it can be very hot. | Warnings: Do not look directly into the lens of the projector during operation to avoid damage to your eyes. | Power consumption (typical): 187 W | Analog signal format system: PAL I | Analog signal format system: SECAM G | AC input voltage: 100 - 240 V | Quantity per pack: 1 pc(s) | Analog signal format system: PAL B | Analog signal format system: PAL G | Supported graphics resolutions: 1280 x 768 (WXGA) | HDMI ports quantity: 1 | Analog signal format system: NTSC | Analog signal format system: NTSC 3.58 | Cables included: AC | Product colour: White | Height: 108 mm | Noise level: 26 dB | Supported graphics resolutions: 1024 x 768 (XGA) | Analog signal format system: PAL | Analog signal format system: SECAM | Analog signal format system: NTSC M | Analog signal format system: PAL M | Analog signal format system: PAL H | Analog signal format system: PAL N | Cable lock slot type: Kensington | Full HD: No | Analog signal format system: NTSC 4.43 | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 800 x 600 (SVGA) | Supported graphics resolutions: 1280 x 800 (WXGA) | Power consumption (max): 225 W | Analog signal format system: SECAM D | HDMI version: 1.4a | Wi-Fi: No |

Native aspect ratio: 4:3 | Analog signal format system: PAL D | Analog signal format system: SECAM

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

B | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 1600 x 1200 (UXGA) | Width: 316 mm | Manual: Yes | Cable lock slot: Yes | AC input frequency: 50/60 Hz | Product type: Desktop projector | USB 2.0 ports quantity: 1 | Analog signal format system: SECAM K | Weight: 3 kg | Depth: 244 mm | Supported graphics resolutions: 1280 x 1024 (SXGA) | Built-in display: No | 3D: Yes | Ethernet LAN: No | On Screen Display (OSD): Yes | Card reader integrated: No | VGA (D-Sub) ports quantity: 2 | Vertical scan range: 50 - 85 Hz | Supported video modes: 480p | Supported video modes: 1080p | Supported video modes: 576p | Supported video modes: 720p | Supported video modes: 576i | Supported video modes: 480i | Power source: AC | Horizontal scan range: 15.38 - 91.15 kHz | DVI port: No | Batteries included: Yes | Supported video modes: 1080i

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903