



TP-Link Omada ES216G network switch Managed L2 Gigabit Ethernet (10/100/1000) Black



Modelis: ES216G

Gamintojas: TP-LINK

EAN: 1210002600682

Prekės kodas: 368642

89.99€

Fast leave: Yes | Compliance certificates: Federal Communications Commission (FCC) | Unified static configuration: Yes | Compliance certificates: RoHS | Compliance certificates: CE | Product colour: Black | Operating temperature (T-T): -5 - 50 °C | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Web-based management: Yes | Cables included: AC | AC input frequency: 50/60 Hz | Operating relative humidity (H-H): 10 - 90% | Firmware upgradeable: Yes | Package type: Box | Power source: AC | User guide: Yes | Networking standards: IEEE 802.3i | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | LED indicators: Yes | Networking standards: IEEE 802.1ab | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | AC input voltage: 100 - 240 V | Storage relative

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

humidity (H-H): 5 - 90% | Power consumption (max): 8.4 W | Power over Ethernet (PoE): No | Zero Touch Provisioning (ZTP): Yes | Surge protection: Yes | Store-and-forward: Yes | Jumbo frames support: Yes | Switch layer: L2 | Height: 44 mm | Forwarding rate: 23.8 Mpps | Cloud-managed: Yes | Auto MDI/MDI-X: Yes | Packet buffer memory: 4 MB | Port mirroring: Yes | Surge protection voltage: 6 kV | Switching capacity: 32 Gbit/s | DHCP features: DHCP client | Flash memory: 64 MB | Basic switching RJ-45 Ethernet ports quantity: 16 | Power connector: AC-in jack | Virtual LAN features: Port-based VLAN | MAC address table: 8000 entries | Auto-negotiation: Yes | Virtual LAN features: MTU VLAN | Rack mount kit: Yes | Link aggregation: Yes | Fanless: Yes | Jumbo frames: 15000 | Number of VLANs: 32 | 10G support: No | Virtual LAN features: Tagged VLAN | Gigabit Ethernet (copper) ports quantity: 16 | Switch type: Managed | Mean time between failures (MTBF): 2131140 h | VLAN support: Yes | IGMP snooping: Yes | Flow control support: Yes | Queue scheduling algorithms: Weighted Round Robin (WRR) | Depth: 140 mm | Rack mounting: Yes | Power supply included: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Heat dissipation: 28.52 BTU/h | Loop protection: Yes | Width: 294 mm

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903