



TP-Link Omada SG5428X network switch Managed L3 Gigabit Ethernet (10/100/1000) Black



Modelis: SG5428X

Gamintojas: TP-LINK

EAN: 8885020626421

Prekės kodas: 368643

462.99€

Networking standards: IEEE 802.3at | Security algorithms: SNMPv2 | Power over Ethernet (PoE): No | Web-based management: Yes | MAC address filtering: Yes | LED indicators: Yes | USB 2.0 ports quantity: 1 | Processor frequency: 1200 MHz | AC input voltage: 100 - 240 V | Firmware upgradeable: Yes | Operating relative humidity (H-H): 10 - 90% | Quick start guide: Yes | Power consumption (max): 19.6 W | Product colour: Black | Networking standards: IEEE 802.3af | AC input frequency: 50/60 Hz | Security algorithms: SNMPv3 | Security algorithms: SNMP | Networking standards: IEEE 802.3bt | Storage relative humidity (H-H): 5 - 90% | Operating temperature (T-T): -5 - 45 °C | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Compliance certificates: RoHS | Compliance certificates: CE | Built-in processor: Yes | Management level: 4 | Flash memory: 512 MB

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

| IP-MAC-Port binding: Yes | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Switching capacity: 128 Gbit/s | Password protection: Yes | Packet buffer memory: 12 MB | Console port: RJ-45 | Power source: AC | Forwarding rate: 95.23 Mpps | Virtual LAN features: Voice VLAN | Virtual LAN features: MAC address-based VLAN | Store-and-forward: Yes | Surge protection: Yes | Jumbo frames support: Yes | Cables included: AC | Surge protection voltage: 6 kV | Link aggregation: Yes | Height: 44 mm | Telnet: Yes | Jumbo frames: 9000 | Basic switching RJ-45 Ethernet ports quantity: 24 | Multicast support: Yes | Depth: 180 mm | Virtual LAN features: Protocol-based VLAN | Bandwidth: 64 Gbit/s | Fanless: Yes | Stackable: Yes | USB Type-C ports quantity: 1 | Power supply included: Yes | DHCP features: DHCP server | Memory type: DRAM | Switch layer: L3 | Gigabit Ethernet (copper) ports quantity: 24 | VLAN support: Yes | Broadcast storm control: Yes | Compliance certificates: Federal Communications Commission (FCC) | MAC address table: 16000 entries | DHCP features: DHCP relay | Port mirroring: Yes | Virtual LAN features: Private VLAN | IGMP snooping: Yes | Number of VLANs: 4000 | Rack mount kit: Yes | ARP inspection: Yes | 10G support: Yes | Static port security: Yes | Width: 440 mm | SSH/SSL support: Yes | Physical stacking (units): 4 | Internal memory: 2000 MB | Rack mounting: Yes | SFP+ module slots quantity: 4 | Access Control List (ACL): Yes | Switch type: Managed | Heat dissipation: 66.87 BTU/h | Mean time between failures (MTBF): 519.543 h | Processor manufacturer: ARM | Cloud-managed: Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903