TP-Link AC1350 Wireless MU-MIMO Gigabit Ceiling Mount Access Point

Modelis: EAP223
Gamintojas: TP-LINK
EAN: 4895252500509
Prekės kodas: 368661

75.00€

Compatible operating systems: Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows11, Linux | Certification: CE, FCC, RoHS | Power over Ethernet (PoE) type supported: Passive PoE | Management platform: Omada | Networking standards: IEEE 802.11a | Storage relative humidity (H-H): 5 - 90% | Power over Ethernet (PoE): Yes | Wireless isolation: Yes | Height: 37.1 mm | Antenna type: Internal | Antennas quantity: 3 | Networking standards: IEEE 802.11b | Operating relative humidity (H-H): 10 - 90% | Width: 205.5 mm | Reset button: Yes | Rate limiting: Yes | Quantity per pack: 1 pc(s) | Mounting kit: Yes | Antenna direction type: Omni-directional | VLAN support: Yes | Placement: Ceiling, Wall | Security algorithms: SSID | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Networking standards: IEEE 802.11ac | Band steering: Yes | Ethernet LAN (RJ-45) ports: 1 | Product colour: White | Operating temperature (T-T): 0 - 40 °C | Number of SSID supported: 15 | 2.4 GHz: Yes | MIMO: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Warnings: Electronic products should be recycled at

specialist electronic waste collection facilities. | Web-based management: Yes | MAC address filtering: Yes | Power over Ethernet (PoE) type supported: Active PoE | Transmitting power (FCC): 24, 22 dBm | 5 GHz: Yes | Warnings: Do not expose to prolonged moisture. | Maximum data transfer rate (2.4 GHz): 450 Mbit/s | Wi-Fi Multimedia (WMM)/(WME): Yes | Power consumption (typical): 9.7 W | 6 GHz: No | Transmitting power (CE): 20, 23 dBm | LED indicators: Power | Maximum data transfer rate (5 GHz): 867 Mbit/s | Quick start guide: Yes | Syslog: Yes | Automatic channel selection: Yes | Depth: 181.5 mm | Automatic channel scanning: Yes | Warnings: Avoid direct contact with water. | Maximum data transfer rate: 867 Mbit/s | Output voltage: 48 V | MIMO type: Multi User MIMO