



Optoma HZ146X-W Standard throw projector 3800 ANSI lumens DLP 1080p (1920x1080) 3D White

Modelis: E9PD7KK01EZ1E

Gamintojas: OPTOMA

EAN: 5055387668201

Prekės kodas: 369202

670.99€

Analog signal format system: PAL H | Analog signal format system: PAL N | Analog signal format system: NTSC 4.43 | USB 2.0 ports quantity: 1 | Power consumption (typical): 88 W | Analog signal format system: SECAM K | Analog signal format system: SECAM G | Cable lock slot type: Kensington | Operating temperature (T-T): 0 - 40 °C | Analog signal format system: PAL I | Analog signal format system: SECAM K1 | Supported video modes: 480p | Supported video modes: 1080p | Analog signal format system: NTSC 3.58 | Analog signal format system: SECAM L | DVI port: No | Analog signal format system: PAL B | Analog signal format system: PAL G | Supported video modes: 576i | Native aspect ratio: 16:9 | Analog signal format system: PAL D | Analog signal format system: SECAM B |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

HDMI ports quantity: 2 | Width: 274 mm | Supported video modes: 720p | Horizontal scan range: 15 - 140 kHz | Power source: AC | Supported video modes: 480i | International Protection (IP) code: IP6X | Analog signal format system: NTSC M | Analog signal format system: PAL M | Analog signal format system: SECAM D | Batteries included: Yes | Supported video modes: 1080i | Supported video modes: 576p | HDMI version: 2.0 | Noise level: 34 dB | Depth: 216 mm | Vertical scan range: 24 - 120 Hz | Cable lock slot: Yes | Package height: 120 mm | Package depth: 250 mm | Audio (L/R) in: 1 | Analog signal format system: SECAM 4.25/4.4 | Analog signal format system: NTSC J | Analog signal format system: PAL 4.43 | Power consumption (max): 139 W | Cables included: Power | Height: 114 mm | Weight: 3 kg | Serial interface type: RS-232 | Product type: Standard throw projector | Manual: Yes | Package weight: 4.2 kg | On Screen Display (OSD): Yes | Product colour: White | Package width: 310 mm | Built-in speaker(s): Yes | Supported aspect ratios: 4:3 | Full HD: Yes | RMS rated power: 15 W | 3D: Yes | Contrast ratio (typical): 2000000:1 | Operating relative humidity (H-H): 0 - 80% | Remote control included: Yes | Focal length range: 12.81 - 16.74 mm | Power consumption (standby): 0.5 W | Commodity code: 8528620000 | Uniformity: 75% | Service life of light source: 30000 h | Keystone correction, horizontal: $\pm 30^\circ$ | Number of colours: 1.073 billion colours | Projector native resolution: 1080p (1920x1080) | Projection distance: 0.8 - 10 m | Supported 3D formats: Frame Sequential | Screen size compatibility: 508 - 7620 mm (20 - 300") | HDMI connector type: Full-size | Projector brightness: 3800 ANSI lumens | Projection technology: DLP | Light source type: Laser | Zoom ratio: 1.1:1 | Offset: 116% | Supported aspect ratios: 16:9 | Throw ratio: 1.48:1 - 1.62:1 | Zoom type: Manual | Keystone correction, vertical: $\pm 30^\circ$ | Supported aspect ratios: 16:10

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903