



**UPS EATON**  
**1800 Watts**  
**2000 VA Wave**  
**form type**  
**Sinewave**  
**OnLine**  
**DoubleConversion**  
**Phase 1phase**  
**Rack 2U**  
**9E2000IR**

Modelis: 9E2000IR

Gamintojas: EATON

EAN: 3553340710346

Prekės kodas: 36981

**938.98€**

- Double conversion topology
- Constantly monitors power conditions and regulates voltage and frequency
- Provides more real power (watts) to protect more equipment with a 0.9 power factor

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- Internal bypass allows service continuity in case of UPS fault
- LCD display
- Long backup time with up to 4 optional EBM

Summary: Eaton 9E2000IR. UPS topology: Double-conversion (Online), Output power capacity: 2 kVA, Output power: 1800 W. AC outlet types: C13 coupler, C14 coupler, Power plug: C13 coupler, AC outlets quantity: 6 AC outlet(s). Battery technology: Lead-Acid, Battery capacity: 7 Ah, Battery voltage: 12 V. Form factor: Tower, Product colour: Black, Rack capacity: 2U. Compliance certificates: CE, Certification: IEC/EN 62040-1 IEC/EN 62040-2 CE | Vendor Homepage: <https://www.eaton.com/gb/en-gb/skuPage.9E2000IR.html> | Audible alarm(s): Yes | Efficiency: 91 | Efficiency (ECO mode): 96.5 | Heat dissipation: 546 | Input frequency: 40/70 | Input operation voltage (max): 276 | Input operation voltage (min): 140 | Input power factor: 99 | Noise level: 45 | Number of input phases: 1 | Number of output phases: 1 | Output frequency: 50/60 | Output operation voltage (max): 240 | Output operation voltage (min): 220 | Output power: 1800 | Output power capacity: 2 | Output power factor: 0.9 | Power source type: AC | UPS topology: Double-conversion (Online) | Waveform: Sine | AC outlet types: C13 coupler/C14 coupler | AC outlets quantity: 6 | Power plug: C13 coupler | RS-232 ports: 1 | Serial interface: Yes | Serial interface type: RS-232 | Serial ports quantity: 1 | USB port: Yes | Battery capacity: 7 | Battery technology: Lead-Acid | Battery voltage: 12 | Number of batteries supported: 6 | Typical backup time at full load: 4.5 | Typical backup time at half load: 12 | Control type: Buttons | Display type: LCD | Form factor: Tower | LED indicators: Yes | Product colour: Black | Rack capacity: 2U | Operating relative humidity (H-H): 0 - 96 | Operating temperature (T-T): 0 - 40 | Cables included: Output power cable,USB cable | Certification: IEC/EN 62040-1 IEC/EN 62040-2 CE | Compliance certificates: CE | Quick installation guide: Yes | Rack mount kit: Yes | Sustainability compliance: Yes | Depth: 608 | Height: 86.5 | Weight: 29900 | Width: 438 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.1041 | Unit Calculated Weight: 32.4