



UPS EATON 680 Watts 850 VA LineInteractive Phase 1phase Rack 1U 5P850IRG2



Modelis: 5P850IRG2

Gamintojas: EATON

EAN: 3553340710308

Prekės kodas: 37006

668.98€

UPS topology Line-Interactive | Output power capacity 0.85 kVA | Output power 680 W | Waveform Sine | Input operation voltage (min) 150 V | Input operation voltage (max) 294 V | Input frequency 47/70 Hz | Output frequency 50/60 Hz | Heat dissipation 307 BTU/h | Number of input phases 1 | Number of output phases 1 | Efficiency 98 % | AC outlet types C13 coupler | Power plug C14 coupler | USB port Yes | Serial interface Yes | Battery technology Sealed Lead Acid (VRLA) | Battery voltage 6 V | Form factor Tower | Colour Black,Silver | Display type LCD | Operating temperature (T-T) 0 - 40 °C | Operating altitude 0 - 3000 m | Weight 13.7 kg Summary: Eaton 5P850IRG2. UPS topology: Line-Interactive, Output power capacity: 0.85 kVA, Output power: 680 W. AC outlet types: C13 coupler, Power plug: C14 coupler, AC outlets quantity: 4 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Battery capacity: 7 Ah, Battery voltage: 6 V. Form factor: Tower, Product colour: Black,

Silver, Rack capacity: 1U. Certification: IEC/EN 62040-1 IEC/EN 62040-2 IEC/EN 62040-3 UL 1778

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

CSA-C22.2 CE UKCA Cm Ukr KCC cTUVus BIS | Vendor Homepage: <https://www.eaton.com/ch/en-gb/skuPage.5P850IRG2.html> | Automatic Voltage Regulation (AVR): Yes | Efficiency: 98 | Heat dissipation: 307 | Input frequency: 47/70 | Input operation voltage (max): 294 | Input operation voltage (min): 150 | Noise level: 35 | Number of input phases: 1 | Number of output phases: 1 | Output frequency: 50/60 | Output operation voltage (max): 240 | Output power: 680 | Output power capacity: 0.85 | UPS topology: Line-Interactive | Waveform: Sine | AC outlet types: C13 coupler | AC outlets quantity: 4 | Power plug: C14 coupler | Serial interface: Yes | Serial interface type: RS-232 | Serial ports quantity: 1 | USB port: Yes | USB port type: USB Type-B | Battery capacity: 7 | Battery technology: Sealed Lead Acid (VRLA) | Battery voltage: 6 | Number of batteries supported: 4 | Display type: LCD | Form factor: Tower | Product colour: Black,Silver | Rack capacity: 1U | Operating altitude: 0 - 3000 | Operating relative humidity (H-H): 0 - 90 | Operating temperature (T-T): 0 - 40 | Certification: IEC/EN 62040-1 IEC/EN 62040-2 IEC/EN 62040-3 UL 1778 CSA-C22.2 CE UKCA Cm Ukr KCC cTUVus BIS | Depth: 509 | Height: 43.2 | Weight: 13700 | Width: 438 | Model: 5P850IRG2 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.05472/0.05516 | Unit Calculated Weight: 18.3

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903