



Zyxel GS1915-8 Managed L2 Gigabit Ethernet (10/100/1000) Black



Modelis: GS1915-8-EU0101F

Gamintojas: ZYXEL

EAN: 4718937621897

Prekės kodas: 370071

75.00€

Certification: CE, FCC, C-Tick, Class A, Class B, BSMI CNS13438 | Auto MDI/MDI-X: Yes | Power connector: AC-in jack | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3at | MIB support: RFC 1213 MIB II, RFC 2819, RFC 1215, RFC 1493 | Switch type: Managed | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | LED indicators: Yes | Weight: 620 g | Jumbo frames: 9000 | Package width: 302 mm | Gigabit Ethernet (copper) ports quantity: 8 | Networking standards: IEEE 802.1x | AC input voltage: 220 - 240 V | Mean time between failures (MTBF): 1144461 h | System event log: Yes | Multicast support: Yes | Storage relative humidity (H-H): 10 - 95% | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Quick start guide: Yes | Power source: AC | Rate limiting: Yes | Power consumption (max): 4.7 W | Switching capacity: 16 Gbit/s | Jumbo frames support: Yes | Web-based management: Yes | MAC address filtering: Yes | Switch layer: L2 | Power over Ethernet (PoE): No | Networking standards: IEEE 802.3ad | Full duplex: Yes | MAC address table: 8000 entries | Copper

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

ethernet cabling technology: 1000BASE-T | Cables included: AC | Basic switching RJ-45 Ethernet ports quantity: 8 | Package depth: 227 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Packet buffer memory: 0.525 MB | 10G support: No | User guide: Yes | SSH/SSL support: Yes | Package weight: 1.1 kg | Width: 250 mm | IGMP snooping: Yes | Harmonized System (HS) code: 85176990 | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3az | Heat dissipation: 16.03 BTU/h | Depth: 104 mm | Broadcast storm control: Yes | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Operating temperature (T-T): 0 - 40 °C | Product colour: Black | Management protocols: SNMP v1,v2,v3, RMON (1,2,3,9) | Package height: 64 mm | Flow control support: Yes | Height: 27 mm | Number of VLANs: 8 | Forwarding rate: 11.9 Mpps | AC input frequency: 50 - 60 Hz | Manual: Yes | Operating relative humidity (H-H): 10 - 95% | Copper ethernet cabling technology: 10BASE-T | VLAN support: Yes | Copper ethernet cabling technology: 100BASE-TX | Electromagnetic compatibility: LVD EN60950-1, BSMI CNS14336-1

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903