



**Zyxel GS1350-
26HP-EU0101F
network switch
Managed L2
Gigabit Ethernet
(10/100/1000)
Power over
Ethernet (PoE)
Grey**

Modelis: GS1350-26HP-EU0101F

Gamintojas: ZYXEL

EAN: 4718937604463

Prekės kodas: 370072

435.99€

AC input frequency: 50 - 60 Hz | Firmware upgradeable: Yes | Web-based management: Yes | Product colour: Grey | Copper ethernet cabling technology: 10BASE-T | Networking standards: IEEE 802.3at | Security algorithms: SSH | Networking standards: IEEE 802.3ad | Security algorithms: SNMP | Operating temperature (T-T): -20 - 50 °C | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Storage relative humidity (H-H): 5 - 95% | Surge protection features: Yes | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.1p | VLAN support: Yes | Total

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Power over Ethernet (PoE) budget: 375 W | Depth: 270 mm | Networking standards: IEEE 802.3x | Copper ethernet cabling technology: 100BASE-TX | AC input voltage: 100 - 240 V | Operating relative humidity (H-H): 5 - 95% | Power over Ethernet (PoE) ports quantity: 24 | Networking standards: IEEE 802.3u | Security algorithms: SNMPv3 | Switching capacity: 52 Gbit/s | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.1w | Cables included: AC | Height: 44 mm | Networking standards: IEEE 802.1ab | Security algorithms: SSL/TLS | Storage temperature (T-T): -40 - 70 °C | Rack mounting: Yes | Harmonized System (HS) code: 85176990 | Weight: 3.58 kg | Noise level: 40.1 dB | LED indicators: Yes | Power consumption (max): 448.9 W | Copper ethernet cabling technology: 1000BASE-T | Power over Ethernet (PoE): Yes | Width: 441 mm | Mean time between failures (MTBF): 888495 h | Port mirroring: Yes | MAC address table: 8000 entries | IGMP snooping: Yes | Packet buffer memory: 0.525 MB | Basic switching RJ-45 Ethernet ports quantity: 24 | DHCP features: DHCP client | DHCP features: DHCP relay | DHCP features: DHCP snooping | Switch layer: L2 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Combo SFP ports quantity: 2 | Number of VLANs: 256 | Heat dissipation: 1530.75 BTU/h | 10G support: No | Switch type: Managed | Rate limiting: Yes | Electromagnetic compatibility: CE, FCC, C-Tick, A BSMI CNS13438 | Multicast support: Yes | Forwarding rate: 38.7 Mpps | Broadcast storm control: Yes | Spanning tree protocol: Yes | Virtual LAN features: MAC address-based VLAN | Fiber ethernet cabling technology: 1000BASE-X | Queue scheduling algorithms: WFQ | Loop protection: Yes | Maximum range: 250 m | Flow control support: Yes | Queue scheduling algorithms: SPQ | Queue scheduling algorithms: Weighted Round Robin (WRR) | System event log: Yes | Configuring Location Settings (CLI): Yes | IGMP proxy: Yes | Virtual LAN features: Port-based VLAN | Rack mount kit: Yes