



**GIGABYTE Z790
EAGLE AX
Motherboard -
Supports Intel
Core 14th Gen
CPUs,
12+1+Phases
Digital VRM, up
to 7600MHz
DDR5 (OC),
3xPCIe 4.0 M.2,
Wi-Fi 6E, 2.5GbE
LAN, USB 3.2
Gen 2**

Modelis: Z790 EAGLE AX

Gamintojas: GIGABYTE

EAN: 4719331860998

Prekės kodas: 371855

170.99€

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Bundled software: Norton® Internet Security (OEM version) LAN bandwidth management software | Maximum internal memory supported by processor: 192 GB | RAID levels: 0 | Battery type: CR2032 | Ethernet interface type: 2.5 Gigabit Ethernet | RAID levels: 5 | Package width: 335 mm | Total number of SATA connectors: 4 | RAID levels: 10 | Number of storage drives supported: 7 | Wi-Fi: Yes | Desktop Management Interface (DMI) version: 2.7 | Number of battery cells: 1 | USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity: 1 | Compatible processor series: Intel® Core™ i5 | Compatible processor series: Intel® Celeron® | RAID levels: 1 | Bluetooth version: 5.3 | Processor socket: LGA 1700 | Processor manufacturer: Intel | Compatible processor series: Intel® Core™ i7 | Compatible processor series: Intel® Core™ i9 | Compatible processor series: Intel® Pentium® Gold | Compatible processor series: Intel® Core™ i3 | PCI Express x16 (Gen 4.x) slots: 1 | Headphone outputs: 1 | CPU fan connector: Yes | Products per shipping (inner) case: 1 pc(s) | TPM connector: Yes | RGB LED pin header: Yes | Number of M.2 (M) slots: 3 | Clear CMOS button: Yes | Top Wi-Fi standard: Wi-Fi 6E (802.11ax) | Number of memory slots: 4 | Ethernet LAN: Yes | Windows operating systems supported: Windows 10 x64 | Depth: 244 mm | WLAN controller model: Intel Wi-Fi 6E AX211 | HDMI ports quantity: 1 | Supported processor sockets: LGA 1700 | Package height: 80 mm | Width: 305 mm | Wi-Fi standards: 802.11b | Number of HDDs supported: 4 | HDMI version: 2.1 | Batteries included: Yes | Battery weight: 3 g | Wi-Fi standards: Wi-Fi 6E (802.11ax) | Wi-Fi standards: Wi-Fi 4 (802.11n) | Supported memory types: DDR5-SDRAM | 12V power connector: Yes | Clear CMOS jumper: Yes | Wi-Fi-AP antenna jack: 2 | Number of EATX power connectors: 2 | Maximum number of SMP processors: 1 | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 4 | Battery technology: Lithium-Manganese Dioxide (LiMnO2) | BIOS type: UEFI AMI | USB connector type: USB Type-A | EPS power connector (8-pin): Yes | Memory channels: Dual-channel | Wi-Fi standards: 802.11g | Memory slots type: DIMM | On-board graphics card: No | Microphone in: Yes | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Antenna included: Yes | Front panel connector: Yes | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Cables included: SATA | USB connector type: USB Type-C | Package depth: 270 mm | PS/2 ports quantity: 1 | Windows operating systems supported: Windows 11 x64 | Height: 35 mm | USB 3.2 Gen 2 (3.1 Gen 2) connectors: 1 | USB 3.2 Gen 2x2 Type-C ports quantity: 1 | Warranty period: 3 year(s) | PCI Express x16 (Gen 5.x) slots: 1 | Supported memory clock speed (max): 7600 MHz | Warnings: Avoid direct contact with electronics to prevent electrostatic damage. | Warnings: Do not dispose of the motherboard in the ordinary rubbish bin the product requires special disposal. | Warnings: Before starting any maintenance or installation, disconnect the product from the power supply. | Lithium weight per battery: 0.07 g | ECC compatibility: ECC & Non-ECC | Number of SATA III connectors: 4 | Ethernet LAN (RJ-45) ports: 1 | Supported memory clock speeds: 7000 |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Supported memory clock speeds: 4800 MHz | Supported memory clock speeds: 6800 | Thunderbolt headers: 2 | Front panel audio connector: Yes | Supported memory clock speeds: 5200 | Maximum internal memory: 192 GB | Supported memory clock speeds: 6600 | Supported memory clock speeds: 6200 | Supported memory clock speeds: 7400 | Supported memory clock speeds: 4400 | Supported memory clock speeds: 7600 MHz | S/PDIF out port: Yes | Supported memory clock speeds: 6000 | Supported memory clock speeds: 5600 | Supported memory clock speeds: 7200 | Audio output channels: 7.1 channels | Country of origin: China | Bluetooth: Yes | Maximum resolution: 4096 x 2304 pixels | HDCP: Yes | Supported memory clock speeds: 6400 | Motherboard chipset: Intel Z790 Express | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 1 | Parallel processing technology support: Not supported | Power source type: ATX | Motherboard form factor: ATX | Supported storage drive interfaces: M.2, SATA III | Supported memory clock speeds: 5800 | Supported memory clock speeds: 5400 | Unbuffered memory: Yes | Supported memory module capacities: 48GB | USB 2.0 connectors: 2 | Supported memory module capacities: 12GB | Audio chip: Realtek ALC897 | Supported memory module capacities: 1GB | Product colour: Bronze | Supported memory module capacities: 2GB | Supported memory module capacities: 4GB | Supported memory module capacities: 8GB | Supported memory module capacities: 32GB | Supported memory module capacities: 16GB | DisplayPort version: 1.2 | RAID support: Yes | PC health monitoring: Voltage | PC health monitoring: Water cooling | Motherboard chipset family: Intel | DisplayPorts quantity: 1 | Supported storage drive types: HDD & SSD | PC health monitoring: Fan | PC health monitoring: Temperature | PCI Express x16 (Gen 3.x) slots: 1 | USB 2.0 ports quantity: 2 | PCI Express x1 (Gen 3.x) slots: 2 | ATX Power connector (24-pin): Yes | Package weight: 1.81 kg