



# TP-Link Tapo C660 KIT - solar- powered outdoor IP surveillance camera



Modelis: Tapo C660KIT

Gamintojas: TP-LINK

EAN: 8885020624199

Prekės kodas: 371920

## 165.99€

Certification: CB, CE, FCC, DOE, CEC, RCM, KC, JFR,VCCI,NCC, BSMI, NTRA, IP65 | Connectivity technology: Wired & Wireless | Product colour: White | Security algorithms: WPA2-PSK | Type: IP security camera | Operating temperature (T-T): -20 - 45 °C | Security algorithms: WPA | AC input voltage: 100 - 240 V | Security algorithms: 128-bit AES | Package weight: 1.5 kg | LED indicators: System | Maximum resolution: 3840 x 2160 pixels | AC input frequency: 50/60 Hz | Package type: Box | Power source type: AC | Reset button: Yes | Built-in microphone: Yes | Security algorithms: SSL/TLS | Width: 185 mm | International Protection (IP) code: IP65 | Number of cameras: 1 | Compatible memory cards: MicroSD (TransFlash) | Remote viewing: Yes | Built-in speaker(s): Yes | Video compression formats: H.264 | Frame rate: 20 fps | Maximum aperture number: 1.6 | Height: 75 mm | Compliance certificates: CE | Compliance certificates: RCM | Alert notification type: Text alert message | Compliance certificates: Federal Communications Commission (FCC) | Placement

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

supported: Outdoor | Compliance certificates: NCC | Virtual assistant: Amazon Alexa & Google Assistant | Compliance certificates: BSMI | Fixed focal length: 4 mm | Compliance certificates: VCCI | Compliance certificates: CB | Night vision: Yes | Compliance certificates: KC | Built-in HDD: No | Wi-Fi standards: 802.11g | LED type: IR | Infrared (IR) cut-off filter: Yes | Optical sensor size: 25.4 / 2.7 mm (1 / 2.7") | Infra-red wavelength: 850 nm | Wi-Fi standards: 802.11b | Form factor: Bullet | Storage temperature (T-T): -20 - 60 °C | Lens viewing angle, diagonal: 105° | Mounting type: Ceiling/wall | Package width: 218 mm | Wi-Fi standards: 802.11a | Sensor type: CMOS | Live view: Yes | Mobile operating systems supported: Android 5.0 | Lens viewing angle, vertical: 45° | Mobile operating systems supported: iOS 9.0 | Mobile operating systems supported: iOS 9.0 | Mobile operating systems supported: iOS 9.0 | Mobile operating systems supported: iOS 9.0 | Mobile operating systems supported: iOS 14 | Mobile operating systems supported: iOS 11.0 | Mobile operating systems supported: iOS 11.0 | Card reader integrated: Yes | Number of lenses: 1 | Mobile operating systems supported: Android 9.0 | Mobile operating systems supported: iOS 10.0 | Mobile operating systems supported: Android 8.0 | Mobile operating systems supported: iOS 13 | Mobile operating systems supported: Android 6.0 | Night vision distance: 12 m | Mobile operating systems supported: Android 4.0 | Mobile operating systems supported: Android 7.0 | Mobile operating systems supported: Android 7.0 | Mobile operating systems supported: iOS 15 | Lens viewing angle, horizontal: 88° | Package depth: 323 mm | Wi-Fi: Yes | Video motion detection: Yes | Package height: 116 mm | Digital zoom: 18x | Total megapixels: 8 MP | Built-in siren: Yes | Operating relative humidity (H-H): 10 - 90% | Mobile operating systems supported: Android 5.0 | Ethernet LAN: Yes | Depth: 147 mm | Storage relative humidity (H-H): 0 - 90% | Wi-Fi standards: Wi-Fi 4 (802.11n) | Video streaming: Yes | Mobile operating systems supported: iOS 12

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903