TP-Link EAP720 wireless access point 4324 Mbit/s White Power over Ethernet (PoE)

Modelis: EAP720

Gamintojas: TP-LINK

EAN: 1210002608732

Prekės kodas: 371923

107.99€

Placement: Ceiling, Wall | DC voltage range: 12 V | Maximum data transfer rate (2.4 GHz): 688 Mbit/s | Channel bandwidth: 240 MHz | Syslog: Yes | Airtime Fairness (ATF): Yes | Height: 36.7 mm | Maximum data transfer rate (5 GHz): 4324 Mbit/s | Internal memory: 4096 MB | Flash memory: 128 MB | Access Control List (ACL): Yes | Cloud-managed: Yes | Remote Authentication Dial-In User Service (RADIUS): Yes | Rate limiting: Yes | Power over Ethernet (PoE) type supported: PoE+ | Width: 160 mm | Schedule access: Yes | Package depth: 228 mm | 6 GHz: No | VLAN support: Yes | Maximum Tx power (5 GHz): 25 dBmW | Guest access: Yes | Access point management: Wi-Fi schedule | BeamForming: Yes | Wi-Fi Multimedia (WMM)/(WME): Yes | Maximum Tx power (2.4 GHz): 25 dBmW | Package height: 65 mm | Depth: 160 mm | Supported network protocols: IPv4/IPv6 | 2.4 GHz: Yes | Antenna type: Internal | Web-based management: Yes | MAC address filtering: Yes | Product colour: White | Spread spectrum method: OFDMA | Maximum data transfer rate: 4324 Mbit/s

| 5 GHz: Yes | Mounting kit: Yes | Compliance certificates: RoHS | Compliance certificates: CE | LED indicators: Yes | DHCP client: Yes | Operating relative humidity (H-H): 10 - 90% | Coverage area: 140 m² | Networking standards: IEEE 802.1x | Networking standards: IEEE 802.3bz | Security algorithms: WPA-Personal | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.11ax | Security algorithms: WPA3-Personal | Networking standards: IEEE 802.11ac | Security algorithms: SNMPv3 | Networking standards: IEEE 802.11v | Security algorithms: EAP-TTLS | Security algorithms: WPA2-Personal | Firmware upgradeable: Yes | Networking standards: IEEE 802.11r | Security algorithms: EAP-FAST | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN (RJ-45) ports: 1 | Security algorithms: SNMP | Ethernet LAN data rates: 2500 | Package width: 245 mm | Input current: 1.5 A | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Networking standards: IEEE 802.11i | Networking standards: IEEE 802.11b | Security algorithms: PEAP | Security algorithms: EAP-SIM | Package weight: 792 g | DC-in jack: Yes | Power over Ethernet (PoE): Yes | Weight: 410 g | Power consumption (max): 17.83 W | AC adapter included: Yes | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.3ab | Security algorithms: SSH | Security algorithms: WPA-Enterprise | Security algorithms: EAP-PEAP | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.11be | Security algorithms: WPA2-Enterprise | Security algorithms: SNMPv2 | Security algorithms: SSID | Security algorithms: WPA3-Enterprise | Reset button: Yes | Networking standards: IEEE 802.11e | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11k | Security algorithms: EAP-MD5 | Networking standards: IEEE 802.11n | Security algorithms: EAP-TLS | Security algorithms: EAP-GTC | Security algorithms: PPSK | Compliance certificates: Industry Canada (IC) | Compliance certificates: Federal Communications Commission (FCC) | Quick start guide: Yes | Security algorithms: EAP-AKA