



TP-Link Omada AX5400 Multi- Gigabit Ceiling Mount WiFi 6 Access Point



Modelis: EAP770

Gamintojas: TP-LINK

EAN: 1210002608718

Prekės kodas: 371924

184.98€

Certification: CE, FCC, RoHS | Width: 220 mm | Band steering: Yes | Rate limiting: Yes | Fit AP mode features: Mesh networking | Maximum data transfer rate (2.4 GHz): 688 Mbit/s | Cabling technology: 10/100/1000/2500Base-T | Automatic channel selection: Yes | DC voltage range: 12 V | VLAN support: Yes | Syslog: Yes | Automatic channel scanning: Yes | Airtime Fairness (ATF): Yes | Depth: 220 mm | Flow control support: Yes | Height: 32.5 mm | MIMO type: Multi User MIMO | Access Control List (ACL): Yes | Maximum data transfer rate (5 GHz): 2882 Mbit/s | Maximum data transfer rate (6 GHz): 5765 Mbit/s | Transmitting power (FCC): 25 dBm (2.4 GHz) 25 dBm (5 GHz) 23 dBm (6 GHz | 6 GHz: Yes | Transmitting power (CE): 20 dBm (2.4 GHz, EIRP) 23 dBm (5 GHz, band 1&band 2, EIRP) 28 dBm (5 GHz, band 3, EIRP) 23dBm (6 GHz, EIRP) | BeamForming: Yes | Ethernet LAN data rates: 100 | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Antenna type: Internal | Reset button: Yes | 5 GHz: Yes | Operating temperature (T-T): 0 - 40 °C | Operating relative humidity (H-H): 10 - 90% | Package type: Box | LED indicators: Yes | Quantity per pack: 1 pc(s) | Ethernet LAN data

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

rates: 1000 Mbit/s | Ethernet LAN data rates: 2500 | Spread spectrum method: OFDMA | Product colour: White | MIMO: Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Web-based management: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.11a | Security algorithms: WPA3-Enterprise | Networking standards: IEEE 802.11ac | Security algorithms: SNMPv3 | Security algorithms: SNMP | Security algorithms: WPA2-Personal | Placement: Ceiling, Wall | Networking standards: IEEE 802.11b | Weight: 730 g | 2.4 GHz: Yes | Quick start guide: Yes | DC-in jack: Yes | Networking standards: IEEE 802.11ax | Input current: 2.5 A | Ethernet LAN (RJ-45) ports: 1 | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Networking standards: IEEE 802.11be | Security algorithms: WPA2-Enterprise | Security algorithms: SNMPv2 | Security algorithms: WPA-Enterprise | Mounting kit: Yes | Security algorithms: WPA-Personal | Storage relative humidity (H-H): 5 - 90% | Power over Ethernet (PoE): Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903