



## DeepCool PL800D power supply unit 800 W 20+4 pin ATX ATX Black

Modelis: R-PL800D-FC0B-EU-V2

Gamintojas: DEEPCOOL

EAN: 6933412721529

Prekės kodas: 372489

---

# 83.99€

---

Certification: CE/FCC/CCC/RCM/EAC/CAN ICES-003(B)/NMB-003(B) /TUV-RH | Efficiency: 85% | Depth: 140 mm | Number of SATA power connectors: 6 | SATA power cable length: 450 | Combined power (-12V): 3.6 W | Power supply unit (PSU) form factor: ATX | Hold time: 16 ms | SATA power cable length: 550 | Product colour: Black | Package type: Box | Operating temperature (T-T): 0 - 40 °C | Number of fans: 1 fan(s) | Motherboard power connector: 20+4 pin ATX | Purpose: PC | SATA power cable length: 650 mm | ATX version: 3.0 | Fan diameter: 12 cm | Motherboard power cable length: 55 cm | PCI Express power connectors (6+2 pin): 3 | Max output current (+5Vsb): 3 A | Peripheral (Molex) power connectors (4-pin): 2 | Power Good signal delay range: 100 - 150 ms | Cooling type: Active | Max output current (-12V): 0.3 A | ATX power connector (20+4 pin): Yes | Height: 86 mm | Max output current (+12V): 54 A | Width: 150 mm | Combined power (+5V): 100 W | Power protection features: Under voltage | Power protection features: Over current | Sustainability compliance: Yes | Power Factor Correction (PFC) type: Active | Fan location: Top | Total power: 800 W | Power

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

protection features: Overheating | Power protection features: Surge protection | Sustainability certificates: Triman | Power protection features: Over power | Max output current (+3.3V): 20 A | Power protection features: No load operation | Combined power (+3.3V): 100 W | On/off switch: Yes | Combined power (+12V): 648 W | Power protection features: Surge & inrush protection (SIP) | PCI Express power connectors (16-pin): 1 | CPU power connector (4+4 pin): Yes | Input current: 9 - 4.5 A | Max output current (+5V): 20 A | Combined power (+5Vsb): 15 W | Power protection features: Over voltage | Bearing technology: HYB | 80 PLUS certification: 80 PLUS Bronze | Mean time between failures (MTBF): 100000 h | AC input voltage: 100 - 240 V | Cabling type: Non-Modular | AC input frequency: 50/60 Hz | Sustainability certificates: ErP | Compliance certificates: WEEE | Compliance certificates: RoHS

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903