



**Mainboard
GIGABYTE AMD
X870E Socket
AM5 ATX RAM
DDR5-SDRAM
4xSlots Wi-Fi
Yes Bluetooth
Yes 4xNumber
of M.2 (M) slots
GIGABYTE X870E
AORUS PRO X3D
X870EAPROX**

Modelis: X870E A PRO X

Gamintojas: GIGABYTE

EAN: 4719331878603

Prekės kodas: 372606

397.99€

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame patikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

GIGABYTE X870E AORUS PRO X3D

Elevate your computing experience with GIGABYTE's renowned motherboard series: AORUS, AERO, and GIGABYTE. Featuring innovative designs and advanced features, these boards offer exceptional performance and reliability. Whether you're a gamer, content creator, or professional, our series cater to your needs, ensuring uncompromising quality and cutting-edge technology.

- X3D Turbo Mode 2.0: Incredible X3D performance unleashed by AI
- Dual Channel DDR5 : 4*DIMMs with AMD EXPO Memory Module Support. DDR5 OC up to 9000MT/s
- AMD Socket AM5 : Supports AMD Ryzen 9000 / 8000 / 7000 Series Processors
- Digital twin 18+2+2 phases VRM solution
- M.2 EZ-Flex : high-efficiency heat dissipation & flexible patented baseplate for M.2 SSD
- WIFI EZ-Plug : Quick and easy design for Wi-Fi antenna installation
- M.2 EZ-Latch Click & Plus : Quick Release & Screwless Design on M.2 slots and heatsinks
- Ultra-Fast Storage : 4*M.2 slots, including PCIe 5.0 x4
- Fast Networking : 5GbE LAN & Wi-Fi 7 with directional Ultra-high gain antenna
- Extended Connectivity : HDMI, Dual USB4 Type-C with DP-Alt, Front QC-USB 65W

Summary: GIGABYTE X870E AORUS PRO X3D Motherboard - Supports AMD Ryzen 9000 CPUs, 18+2+2 Phases Digital VRM, up to 9000Hz DDR5 (OC), 2xPCIe 5.0 + 2xPCIe 4.0, Wi-Fi 7, 5GbE LAN, USB 4. Processor manufacturer: AMD, Processor socket: Socket AM5, Compatible processor series: AMD Ryzen 7000 Series, AMD Ryzen 8000 Series, AMD Ryzen 9000 Series. Supported memory types: DDR5-SDRAM, Maximum internal memory: 256 GB, Memory slots type: DIMM. Supported storage drive interfaces: M.2, PCI Express 4.0, PCI Express 5.0, SATA III, Supported storage drive types: HDD & SSD, RAID levels: 0, 1, 5, 10. Maximum resolution: 4096 x 2304 pixels. Ethernet interface type: 2.5 Gigabit Ethernet, 5 Gigabit Ethernet, Fast Ethernet, Gigabit Ethernet, LAN controller: Realtek RTL8126, Top Wi-Fi standard: Wi-Fi 7 (802.11be) | Vendor Homepage: <https://www.gigabyte.com/Motherboard/X870E-AORUS-PRO-X3D> | Audio chip: Realtek ALC1220-VB | Audio output channels: 7.1 | Component for: PC | Cooling type: Passive | Motherboard chipset: AMD X870E | Motherboard chipset family: AMD | Motherboard form factor: ATX | PC health monitoring: CPU/Fan/Temperature/Voltage/Water cooling | Power source type: ATX | Product colour: Black | Windows operating systems supported: Windows 11 x64 | Compatible processor series: AMD Ryzen

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš išsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

7000 Series/AMD Ryzen 8000 Series/AMD Ryzen 9000 Series | Processor manufacturer: AMD | Processor socket: Socket AM5 | Supported processor sockets: Socket AM5 | ECC compatibility: Non-ECC | Maximum internal memory: 256 | Maximum internal memory per slot: 64 | Memory channels: Dual-channel | Memory slots type: DIMM | Number of memory slots: 4 | Supported memory clock speed (max): 9000 | Supported memory clock speeds: 4800/5200/5600/6000/6200/6400/6600/6800/7000/7200/7600/7800/8000/8200/8400/8600/8800/9000 | Supported memory types: DDR5-SDRAM | Unbuffered memory: Yes | Number of HDDs supported: 4 | Number of storage drives supported: 8 | RAID levels: 0/1/10/5 | RAID support: Yes | Supported storage drive interfaces: M.2,PCI Express 4.0,PCI Express 5.0,SATA III | Supported storage drive types: HDD & SSD | DirectX version: 12.0 | HDCP: Yes | HDCP version: 2.3 | Maximum resolution: 4096 x 2304 | Parallel processing technology support: Not supported | ATX Power connector (24-pin): Yes | CPU fan connector: Yes | EPS power connector (8-pin): Yes | Front panel audio connector: Yes | Front panel connector: Yes | Number of chassis fan connectors: 6 | Number of CPU fan connectors: 2 | Number of EPS power connectors (8-pin): 2 | Number of noise detection headers: 1 | Number of RGB LED pin headers: 4 | Number of SATA III connectors: 4 | Number of temperature sensor headers: 2 | Number of water pump connectors: 3 | RGB LED pin header: Yes | TPM connector: Yes | USB 2.0 connectors: 2 | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 2 | USB 3.2 Gen 2x2 connectors: 1 | Digital audio optical out: 1 | DisplayPort version: 1.4 | Ethernet LAN (RJ-45) ports: 1 | HDMI ports quantity: 1 | HDMI version: 2.1 | Headphone outputs: 1 | Line-in: Yes | S/PDIF out port: Yes | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 3 | USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity: 5 | USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity: 2 | USB4 Gen 2x2 ports quantity: 2 | WiFi-AP antenna jack: 2 | Bluetooth: Yes | Bluetooth version: 5.4 | Ethernet interface type: 2.5 Gigabit Ethernet/5 Gigabit Ethernet/Fast Ethernet/Gigabit Ethernet | Ethernet LAN: Yes | LAN controller: Realtek RTL8126 | Top Wi-Fi standard: Wi-Fi 7 (802.11be) | Wi-Fi: Yes | Wi-Fi standards: 802.11a/802.11b/802.11g/Wi-Fi 4 (802.11n)/Wi-Fi 5 (802.11ac)/Wi-Fi 6 (802.11ax)/Wi-Fi 6E (802.11ax)/Wi-Fi 7 (802.11be) | WLAN controller model: Qualcomm QCNM865 | 1st M.2 highest PCI Express generation: 5.0 | 1st M.2 largest key size: 25110 | 2nd M.2 highest PCI Express generation: 5.0 | 2nd M.2 largest key size: 22110 | 3rd M.2 highest PCI Express generation: 4.0 | 3rd M.2 largest key size: 22110 | 4th M.2 highest PCI Express generation: 4.0 | 4th M.2 largest key size: 22110 | Number of M.2 (M) slots: 4 | PCI Express x16 (Gen 3.x) slots: 1 | PCI Express x16 (Gen 4.x) slots: 1 | PCI Express x16 (Gen 5.x) slots: 1 | ACPI version: 5.0 | BIOS memory size: 512 | BIOS type: UEFI AMI | Clear CMOS button: Yes | Clear CMOS jumper: Yes | Desktop Management Interface (DMI) version: 2.7 | System Management BIOS (SMBIOS) version: 2.7 | Battery capacity: 220 | Battery technology: Lithium-Manganese Dioxide

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

(LiMnO₂) | Battery type: CR2032 | Battery weight: 3 | Country of origin: Taiwan | Lithium weight per battery: 0.07 | Number of battery cells: 1 | Package depth: 294 | Package height: 80 | Package weight: 4250 | Package width: 345 | Products per shipping (inner) case: 1 | Depth: 244 | Height: 35 | Width: 305 | Antenna included: Yes | Batteries included: Yes | Screws included: Yes | Warranty period: 3 | Weight: 3730 | Model: GIGABYTE X870E AORUS PRO X3D | Units per Pallet: 0 | Units per Shipping Box: 3 | Unit Calculated Volume: 0.0147 | Unit Calculated Weight: 4.27

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903