



Zyxel GS1920-48HPV2 Managed Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Black

Modelis: GS192048HPV2-EU0101F

Gamintojas: ZYXEL

EAN: 4718937601974

Prekės kodas: 372689

689.99€

Certification: RoHS | Warnings: Follow the safety guidelines for electrical current. | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Avoid contact of the device with liquid. | Virtual LAN features: IP subnet-based VLAN | 10G support: No | Queue scheduling algorithms: WFQ | Virtual LAN features: Voice VLAN | Multicast support: Yes | Virtual LAN features: Protocol-based VLAN | Authentication: Guest VLAN, Port-based authentication | Rack mount kit: Yes | Authentication type: IEEE 802.1x, RADIUS | IP-MAC-Port binding: Yes | ARP inspection: Yes | System event log: Yes | DHCP features: DHCPv6 relay | IGMP snooping: Yes | DHCP features: DHCP snooping | Virtual LAN features: MAC address-based VLAN | Fiber ethernet cabling technology: 1000BASE-X |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Harmonized System (HS) code: 85176990 | Electromagnetic compatibility: FCC 15 A, CE A, BSMI EMC | DHCP features: DHCP client | DHCP features: DHCP relay | Virtual LAN features: Private VLAN | Virtual LAN features: Port-based VLAN | Flow control support: Yes | Queue scheduling algorithms: SPQ | Queue scheduling algorithms: Weighted Round Robin (WRR) | Packet buffer memory: 1.5 MB | Spanning tree protocol: Yes | Safety: LVD, BSMI | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Switching capacity: 100 Gbit/s | Mean time between failures (MTBF): 502509 h | Forwarding rate: 74 Mpps | Switch type: Managed | Rate limiting: Yes | MAC address table: 16000 entries | Combo SFP ports quantity: 4 | Access Control List (ACL): Yes | Heat dissipation: 1617.36 BTU/h | Copper ethernet cabling technology: 100BASE-TX | Copper ethernet cabling technology: 1000BASE-T | Basic switching RJ-45 Ethernet ports quantity: 44 | CPU defense: Yes | Fiber optic connector: SFP | SFP module slots quantity: 2 | Password protection: Yes | Operating relative humidity (H-H): 10 - 95% | Power over Ethernet (PoE) ports quantity: 48 | AC input frequency: 50 - 60 Hz | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Security algorithms: SNMP | Package width: 616 mm | Networking standards: IEEE 802.1ab | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Operating temperature (T-T): 0 - 50 °C | Networking standards: IEEE 802.3u | Security algorithms: SNMPv3 | Power over Ethernet (PoE): Yes | Width: 441 mm | Rack mounting: No | Networking standards: IEEE 802.1x | Storage relative humidity (H-H): 10 - 95% | Package weight: 5.25 kg | Total Power over Ethernet (PoE) budget: 375 W | Package height: 107 mm | VLAN support: Yes | AC input voltage: 100 - 240 V | Internal memory: 256 MB | Depth: 270 mm | Noise level: 26.5 dB | Height: 44 mm | Product colour: Black | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Flash memory: 32 MB | MAC address filtering: Yes | Security algorithms: 802.1x RADIUS | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Package depth: 355 mm | Cables included: AC | Networking standards: IEEE 802.1w | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Power consumption (max): 474.3 W | Weight: 4.1 kg