



CyberPower BR1000ELCD-FR uninterruptible power supply (UPS) Line- Interactive 1 kVA 600 W 8 AC outlet(s)

Modelis: BR1000ELCD-FR

Gamintojas: CYBERPOWER

EAN: 4712856271249

Prekės kodas: 372702

143.99€

Certification: CE | Operating relative humidity (H-H): 0 - 90% | Ethernet LAN (RJ-45) ports: 2 | Product colour: Black | Cable length: 1.5 m | Storage temperature (T-T): -20 - 50 °C | Operating temperature (T-T): 0 - 40 °C | AC outlets quantity: 8 AC outlet(s) | Operating altitude: 0 - 3000 m | Form factor: Compact | Storage relative humidity (H-H): 0 - 90% | USB 2.0 ports quantity: 1 | LED indicators: Yes | Response time: 4 ms | Weight: 6.5 kg | Typical backup time at full load: 1 min | Surge protection features: Network | Surge protection features: Telephone | Power protection features: Overload | Waveform: Sine | Surge protection features: Modem | Surge protection features: Fax | Surge protection features: Digital Subscriber Line (DSL) | Input operation voltage (max): 290 V | Display

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

type: LCD | UPS topology: Line-Interactive | Output power capacity: 1 kVA | Height: 118 mm |
Housing material: Plastic | Input operation voltage (min): 165 V | Automatic Voltage Regulation
(AVR): Yes | Non-operating altitude: 0 - 3000 m | Output power: 600 W | Battery recharge time: 8 h |
Output frequency: 50/60 Hz | USB port: Yes | Modem (RJ-11) ports: 2 | AC outlet types: Type E | Cold
start: Yes | Depth: 288 mm | Warnings: Use the appliance in well-ventilated areas to avoid
overheating. | Audible alarm(s): Yes | Warnings: Do not disassemble the unit housing, there may be a
risk of electric shock. | EMI/RFI noise filtering: Yes | Width: 166 mm | Warnings: Keep away from
sources of fire and water. | Audible alarm modes: Alarm when on battery, Fault, Low battery alarm,
Overload alarm | Compliance certificates: RoHS | Battery technology: Sealed Lead Acid (VRLA) |
Surge energy rating: 125 J | Input frequency: 50/60 Hz | Typical backup time at half load: 6 min |
Surge protection: Yes

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903