



Ubiquiti UniFi Pro HD 24 Managed L2/L3 2.5G Ethernet (100/1000/2500) 1U Grey



Modelis: USW-Pro-HD-24

Gamintojas: UBIQUITI

EAN: 810084696637

Prekės kodas: 372732

590.00€

Compliance certificates: Industry Canada (IC) | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: CE | Quality of Service (QoS) support: Yes | MAC address table: 32000 entries | Width: 442.4 mm | Display type: LCM | Power over Ethernet (PoE): No | AC input frequency: 50/60 Hz | DHCP features: DHCP server | LED indicators: Speed | Form factor: 1U | DHCP features: DHCP relay | AC input voltage: 100 - 240 V | LED indicators: Link | Depth: 285 mm | Product colour: Grey | Cables included: Power | Height: 44 mm | Multicast support: Yes | LED indicators: Status | DHCP features: DHCP guarding | VLAN support: Yes | Basic switching RJ-45 Ethernet ports quantity: 22 | Number of VLANs: 1000 | Jumbo frames support: Yes | Networking standards: IEEE 802.1x | Power supply included: Yes | 10G support: Yes | Power consumption (max): 60 W | Redundant power supply (RPS) support: Yes | Housing material: SGCC | Weight: 4.2 kg | Reset button: Yes | Switching capacity: 230 Gbit/s | Power connector: AC/DC | DHCP features: DHCP

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

snooping | Operating relative humidity (H-H): 10 - 90% | Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500) | Packet buffer memory: 2 MB | IGMP snooping: Yes | Operating temperature (T-T): -5 - 40 °C | Rack mounting: Yes | Power source: AC/DC | Throughput: 115 Gbit/s | Broadcast storm control: Yes | Flow control support: Yes | Rack mount kit: Yes | Static route: Yes | Virtual LAN features: Voice VLAN | Loop protection: Yes | Forwarding rate: 171.12 Mpps | Rate limiting: Yes | Heat dissipation: 102.36 BTU/h | SFP+ module slots quantity: 4 | Stackable: Yes | Switch layer: L2/L3 | Port mirroring: Yes | Switch type: Managed | 2.5G Ethernet (copper) ports quantity: 22 | 10G Ethernet (copper) ports quantity: 2 | IPv4 routes: 12000

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903