



be quiet! POWER ZONE 2 850W power supply unit 20+4 pin ATX ATX Black



Modelis: BP007EU

Gamintojas: BE QUIET!

EAN: 4260052191378

Prekės kodas: 372899

157.99€

Shipping (inner) case width: 28.2 cm | Efficiency: 92.3% | AC input voltage: 100 - 240 V | Depth: 160 mm | Power factor: 0.98 | Width: 150 mm | Noise level: 24.9 dB | Purpose: PC | Total power: 850 W | Storage temperature (T-T): -40 - 70 °C | Package weight: 3.21 kg | Shipping (inner) case height: 34.6 cm | Screws included: Yes | 80 PLUS certification: 80 PLUS Platinum | EPS power connector (8-pin): Yes | Cabling type: Fully-Modular | Package width: 248 mm | Mean time between failures (MTBF): 100000 h | Storage relative humidity (H-H): 0 - 95% | Package depth: 328 mm | Shipping (inner) case gross weight: 19.3 kg | Number of fans: 1 fan(s) | Product colour: Black | Power supply unit (PSU) form factor: ATX | Cooling type: Active | Power protection features: Short circuit | Power protection features: Over voltage | Fan diameter: 14 cm | Power protection features: Over power | Number of +12V rail(s): 1 | Power protection features: Under voltage | Power protection features: Over current |

Shipping (inner) case length: 65.1 cm | Operating temperature (T-T): 0 - 40 °C | Peripheral (Molex)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

power connectors (4-pin): 1 | PCI Express power connectors (6+2 pin): 3 | Products per shipping (inner) case: 6 pc(s) | Power protection features: Overheating | Height: 86 mm | Power protection features: Surge & inrush | On/off switch: Yes | AC input frequency: 50/60 Hz | Package type: Box | Operating relative humidity (H-H): 0 - 85% | Manual: Yes | Package height: 102 mm | Hold time: 21.1 ms | Combined power (+5Vsb): 15 W | Maximum input current (@220V): 5 A | Maximum input current (@110V): 10 A | CPU power connector (4+4 pin): Yes | Motherboard power connector: 20+4 pin ATX | ATX version: 3.1 | SATA power cable length: 550 | Bearing technology: Rifle | SATA power cable length: 1000 mm | CPU power cable length: 70 cm | Max output current (+5V): 20 A | PCI Express power cable length: 60 cm | Max output current (-12V): 0.5 A | SATA power cable length: 700 | SATA power cable length: 850 mm | Cable ties included: Yes | Combined power (-12V): 6 W | Combined power (+3.3V): 120 W | Max output current (+12V): 70.8 A | CPU P4 connector (4-pin): 1 | Number of SATA power connectors: 7 | Peak power: 920 W | Waste Electrical and Electronic Equipment (WEEE) compliance: Yes | EPS version: 2.92 | Manual languages: Polish | Max output current (+5Vsb): 3 A | Combined power (+5V): 120 W | Max output current (+3.3V): 20 A | Motherboard power cable length: 60 cm | Manual languages: Spanish | Sustainability certificates: ENERGY STAR | Sustainability certificates: ErP | Manual languages: Russian | Sustainability certificates: Triman | Manual languages: English | Peripheral (Molex) power cable length: 1000 | Combined power (+12V): 849.6 W | Manual languages: French | Manual languages: Ukrainian | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: WEEE | Compliance certificates: RCM | Compliance certificates: TÜV mark | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: BSMI | Manual languages: German | Compliance certificates: CB | Compliance certificates: UKCA | Compliance certificates: CCC | PCI Express power connectors (16-pin): 1

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903