

Asrock B450M Pro4 R2.0 AMD B450 Socket AM4 micro ATX

Gamintojas: **ASROCK** · Modelis: **B450M PRO4 R2.0** · EAN: **4710483932793** · Prekės kodas: **373217**



71,90 €

Kaina su PVM

Be PVM: **59,42 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt



Aprašymas

Bundled software: ASRock A-Tuning ASRock Polychrome SYNC ASRock XFast LAN | RAID levels: 1 | Motherboard chipset: AMD B450 | Wake-on-LAN ready: Yes | Supported storage drive types: HDD & SSD | Graphics card family: AMD | Cables included: SATA | Front panel audio connector: Yes | RAID levels: 10 | EPS power connector (8-pin): Yes | Memory channels: Dual-channel | Motherboard chipset family: AMD | Ethernet interface type: Gigabit Ethernet | TPM connector: Yes | USB connector type: USB Type-C | RAID levels: 0 | Supported memory clock speeds: 3200 | USB connector type: USB Type-A | Width: 244 mm | RAID support: Yes | Supported memory types: DDR4-SDRAM | CPU fan connector: Yes | Windows operating systems supported: Windows 11 x64 | Motherboard form factor: micro ATX | Chassis intrusion connector: Yes | HDMI ports quantity: 1 | Supported memory clock speeds: 2933 | On-board graphics card: Yes | PC health monitoring: Temperature | USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity: 1 | RGB LED pin header: Yes | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 4 | Front panel connector: Yes | BIOS type: UEFI AMI | Audio output channels: 7.1 channels | Maximum internal memory: 128 GB | Memory slots type: DIMM | Microphone in: Yes | Supported storage drive interfaces: M.2, PCI Express 3.0, SATA III | PC health monitoring: Fan | Windows operating systems supported: Windows 10 x64 | Headphone outputs: 1 | HDCP: Yes | Number of SATA III connectors: 4 | ATX Power connector (24-pin): Yes | HDMI version: 1.4 | Audio chip: Realtek ALC892 / Realtek ALC897 | Wi-Fi: No | Number of M.2 (M) slots: 1 | Ethernet LAN (RJ-45) ports: 1 | Number of COM connectors: 1 | Drivers included: Yes | USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity: 1 | Processor manufacturer: AMD | DirectX version: 12.0 | USB 2.0 ports quantity: 2 | Compatible processor series: AMD Ryzen™ 5 | LAN controller: Realtek RTL8111H | Compatible processor series: AMD Ryzen™ 3 | PCI Express x16 (Gen 3.x) slots: 1 | Ethernet LAN: Yes | Depth: 244 mm | PC health monitoring: Voltage | Maximum resolution: 4096 x 2160 pixels | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 1 | Number of displays supported: 3 | Compatible processor series: AMD Ryzen™ 7 | Supported memory clock speeds: 2400 | VGA (D-Sub) ports quantity: 1 | Number of memory slots: 4 | Supported memory clock speeds: 2133 | Number of chassis fan connectors: 3 | Supported memory clock speeds: 2667 | DVI-D ports quantity: 1 | Unbuffered memory: Yes | Processor socket: Socket AM4 | USB 2.0 connectors: 2 | PCI Express x16 (Gen 2.x) slots: 1 | Power source type: ATX | Parallel processing technology support: Quad-GPU CrossFireX | Parallel processing technology support: CrossFireX

Techninė specifikacija

Specifications

Sandėlio grupė Enterprise and server products > Motherboards > Motherboards Socket-AM4 [+0][-0]

Matmenys ir svoris

Matmenys (I × P × A) 6,00cm × 28,00cm × 26,00cm

Svoris 1,17kg