



DeepCool PL750D WH power supply unit 750 W 20+4 pin ATX ATX White

Modelis: R-PL750D-FC0W-EU-V2

Gamintojas: DEEPCOOL

EAN: 6933412721437

Prekės kodas: 373456

73.99€

Certification: CE/FCC/CCC/RCM/EAC/CAN ICES-003(B)/NMB-003(B) /TUV-RH | Cooling type: Active | Width: 150 mm | Efficiency: 85% | Power protection features: Over power | Cabling type: Non-Modular | Bearing technology: HYB | Combined power (+3.3V): 100 W | ATX power connector (20+4 pin): Yes | Input current: 10 - 5 A | Peripheral (Molex) power connectors (4-pin): 2 | Operating temperature (T-T): 0 - 40 °C | Power protection features: Over voltage | Power Factor Correction (PFC) type: Active | 80 PLUS certification: 80 PLUS Bronze | Mean time between failures (MTBF): 100000 h | AC input voltage: 100 - 240 V | Power protection features: No load operation | PCI Express power connectors (6+2 pin): 3 | Power supply unit (PSU) form factor: ATX | Depth: 140 mm | Number of fans: 1 fan(s) | CPU power connector (4+4 pin): Yes | Fan diameter: 12 cm | Power protection features: Under voltage | Power protection features: Over current | Total power: 750 W | Fan

location: Top | Max output current (+12V): 62.5 A | Height: 86 mm | Power protection features:

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Overheating | Power protection features: Surge protection | On/off switch: Yes | Product colour: White | Hold time: 16 ms | Combined power (-12V): 3.6 W | ATX version: 3.1 | AC input frequency: 50/60 Hz | Combined power (+5V): 100 W | Purpose: PC | Package type: Box | Max output current (+5V): 20 A | Max output current (-12V): 0.3 A | Power protection features: Surge & inrush protection (SIP) | Power Good signal delay range: 100 - 150 ms | Max output current (+3.3V): 20 A | Motherboard power connector: 20+4 pin ATX | Combined power (+5Vsb): 15 W | Max output current (+5Vsb): 3 A | Combined power (+12V): 750 W | Number of SATA power connectors: 7 | Sustainability certificates: ErP | Sustainability certificates: Triman | PCI Express power connectors (16-pin): 1 | Sustainability compliance: Yes | Compliance certificates: WEEE | Compliance certificates: RoHS

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903