



ASUS TUF GAMING A520M- PLUS II AMD A520 Socket AM4 micro ATX

Modelis: 90MB17G0-M0EAY0

Gamintojas: ASUS

EAN: 4711081154457

Prekės kodas: 373830

95.99€

ECC compatibility: ECC | Warnings: Dispose of according to local electro-waste regulations. | Warnings: Store away from water and sources of moisture. | Number of audio jack connectors: 3 | Warnings: Avoid direct contact with sensitive electronic components. | USB connector type: USB Type-A | Ethernet LAN (RJ-45) ports: 1 | Number of COM connectors: 1 | Supported memory clock speeds: 2400 | Supported memory clock speeds: 2800 | Supported storage drive interfaces: M.2, PCI Express 3.0, SATA III | Number of SATA III connectors: 4 | USB 2.0 ports quantity: 2 | Motherboard chipset family: AMD | DisplayPorts quantity: 1 | Supported memory clock speeds: 3000 | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 1 | Supported memory clock speeds: 3733 | Supported memory clock speeds: 4400 | Supported memory clock speeds: 3333 | Supported memory clock speeds: 4466 | Parallel processing technology support: Not supported | BIOS type: UEFI AMI | EPS power connector (8-pin): Yes | RAID levels: 1 | Wake-on-LAN ready: Yes | Supported storage drive types: HDD & SSD | USB 2.0 connectors: 2 | Motherboard chipset: AMD A520 | Front panel audio connector: Yes | Audio

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

chip: Realtek ALC887 / Realtek ALC897 | PCI Express x1 (Gen 3.x) slots: 2 | RAID levels: 10 | Supported memory clock speeds: 4600 | Supported memory clock speeds: 3600 | Supported memory clock speeds: 3200 MHz | Supported memory clock speeds: 2666 | Supported memory clock speeds: 4266 | PCI Express x16 (Gen 3.x) slots: 1 | Supported memory clock speeds: 2133 | Supported memory clock speeds: 4133 | Supported memory clock speeds: 4000 | Supported memory clock speeds: 4800 MHz | S/PDIF out connector: Yes | Audio output channels: 7.1 channels | DisplayPort version: 1.2 | Number of M.2 (M) slots: 1 | Number of M.2 (M) slots: 1 | Unbuffered memory: Yes | Supported memory clock speeds: 3866 | Maximum internal memory: 128 GB | Windows operating systems supported: Windows 10 x64 | Supported processor sockets: Socket AM4 | CPU fan connector: Yes | Number of chassis fan connectors: 2 | Maximum resolution: 3840 x 2160 pixels | Supported memory clock speeds: 3466 | RAID levels: 0 | ATX Power connector (24-pin): Yes | Processor socket: Socket AM4 | Ethernet interface type: Gigabit Ethernet | Number of storage drives supported: 5 | HDMI ports quantity: 1 | Compatible processor series: AMD Ryzen 3000 Series | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 4 | Wi-Fi: No | RGB LED pin header: Yes | Drivers included: Yes | PS/2 ports quantity: 1 | Memory channels: Dual-channel | TPM connector: Yes | Cables included: SATA | VGA (D-Sub) ports quantity: 1 | Number of memory slots: 4 | 12V power connector: Yes | Processor manufacturer: AMD | Supported memory types: DDR4-SDRAM | Memory slots type: DIMM | Compatible processor series: AMD Ryzen 5000 Series | Ethernet LAN: Yes | Clear CMOS jumper: Yes | HDMI version: 2.1