



## Hikvision DS-3E0310HP-E network links Non-managed Fast Ethernet (10/100) PoE support Blue

Modelis: DS-3E0310HP-E

Gamintojas: HIKVISION

EAN: 6954273693350

Prekės kodas: 374044

# 72.99€

Height: 27.8 mm | Switching capacity: 5.6 Gbit/s | Total Power over Ethernet (PoE) budget: 110 W | Power over Ethernet (PoE): Yes | Power consumption (max): 120 W | Operating temperature (T-T): -10 - 55 °C | Product colour: Blue | LED indicators: Yes | Storage temperature (T-T): -40 - 85 °C | Weight: 550 g | Operating relative humidity (H-H): 5 - 95% | Auto MDI/MDI-X: Yes | Width: 217.6 mm | Basic switching RJ-45 Ethernet ports quantity: 8 | Power consumption (typical): 10 W | Power over Ethernet (PoE) ports quantity: 8 | Package weight: 1.22 kg | Networking standards: IEEE 802.3 | Full duplex: Yes | 10G support: No | Depth: 103.3 mm | Input current: 2.5 A | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3bt | Power over Ethernet (PoE) power per port: 60 W | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.3af | Housing material: Metal |

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3z | Storage relative humidity (H-H): 5 - 95% | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | Networking standards: IEEE 802.3ab | Warnings: Ensure the unit is adequately ventilated during operation. | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Warnings: Do not open the case or try to repair it yourself. | Store-and-forward: Yes | Switch type: Unmanaged | MAC address table: 16000 entries | DC input voltage: 48 V | Forwarding rate: 4.166 Mpps | Gigabit Ethernet (copper) ports quantity: 2