



# CPU COOLER S\_MULTI/G89.GA2L36PB.00 LIAN LI



Modelis: G89.GA2L36PB.00

Gamintojas: LIAN LI

EAN: 4718466016645

Prekės kodas: 374252

## 99.99€

### HIGH-PERFORMANCE PUMP

The compact GA II Lite pump reaches speeds of up to 3800 RPM, providing powerful cooling for efficient CPU temperature management.

Compared to the GA II LCD, the GA II Lite 360R and 240R pump achieved better CPU average temperature.

### ROTATABLE LOGO

Each pump includes a removable logo lid, allowing the logo orientation to adjust to any setup.

### STUNNING PUMP LIGHTING

Featuring 16 LEDs beneath the pump cap, paired with dual infinity mirror rings and the outer

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903

diffuser, the pump head illuminates with eye-catching, multi-layered lighting effects that enhance your build's aesthetics.

## HIGH DENSITY ALUMINUM RADIATOR

At 27mm thick, the high-density aluminum radiator maximizes surface area for effective heat dissipation.

- Available in 360mm and 240mm radiator sizes, ensuring versatile compatibility for various system configurations
- High-performance pump design operating at 3800 RPM for optimal thermal management
- Customizable ARGB blockhead with a rotatable logo
- 28mm RGB or PBT performance fans capable of reaching speeds up to 2500 RPM for efficient cooling
- Compatible with platforms including LGA1700/ LGA1851/ AM4/ AM5

Summary: Lian Li GA II LITE. Type: Liquid cooling kit, Fan diameter: 12 cm, Rotational speed (min): 200 RPM, Rotational speed (max): 2500 RPM, Minimum air pressure: 5 mmH2O, Bearing type: Fluid Dynamic Bearing (FDB). Product colour: Black | Vendor Homepage: <https://lian-li.com/product/ga-ii-lite/> | Bearing type: Fluid Dynamic Bearing (FDB) | Fan diameter: 120 | Maximum airflow: 73.14 | Minimum air pressure: 5 | Noise level (high speed): 29.8 | Rotational speed (max): 2500 | Rotational speed (min): 200 | Suitable location: Processor | Supported processor sockets: LGA 1700/LGA 1851/Socket AM4/Socket AM5 | Type: Liquid cooling kit | Illumination colour: Multi | Number of fans: 3 | Product colour: Black | Radiator material: Aluminum | Fan dimensions (W x D x H): 124 x 120 x 28 | Radiator depth: 120 | Radiator height: 27 | Radiator width: 397 | Tube length: 400 | Warranty period: 6 | Model: GA2L36PB | Model name: GA II Lite | Units per Pallet: 0 | Units per Shipping Box: 4 | Unit Calculated Volume: 0.01666 | Unit Calculated Weight: 2.65

---

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

[www.shopro.lt](http://www.shopro.lt) | [info@shopro.lt](mailto:info@shopro.lt) | +370 693 39903