



UPS TECNOWARE 1000 VA Phase 1 phase FGCERAPLS1002SCH

Modelis: FGCERAPLS1002SCH

Gamintojas: TECNOWARE

EAN: 8026475176363

Prekės kodas: 37426

92.99€

UPS ERA PLUS STRIP 1000VA TOGETHER ON. Line interactive plus technology. Dimensions 20x10x34,5 cm, weight 4,4 kg, Backup time up to 20 min. Designed for PCs, printers, telematic cash registers and pos. It has 4 schuko/italian 10A type outputs protected against blackout, overvoltages and undervoltages and 4 schuko /italian 10A type outputs protected against overvoltages and undervoltages. Equipped with LED for signaling the operating status and a USB interface for UPS control and on/off programming via the free Tecnomanager software.

- Complete protection against blackout and power surges (overvoltages and undervoltages)
- Recommended for Personal Computers, DVR / NVR and video surveillance systems, ADSL / fiber modem, switch / router, cash registers

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- Not suitable with power supplies with Active PFC circuit (Server, PC game, video game console, workstation, Mac computer), lamps and electric motors
- AVR Automatic Voltage Regulator electronic circuit
- n°8 Italian/Schuko output sockets and n°1 schuko input cable
- n°4 sockets outlets protected against blackout
- n°4 sockets outlets protected against overvoltages
- Multifunction LED and on-off button
- USB port for UPS control and monitoring and on / off programming via Tecnomanager software
- USB on the front for fast smartphone/tablet charging
- UPS TecnoManager management software compatible with Windows, Mac OS X, Linux etc

Summary: Tecnoware Era Plus Strip 1000. UPS topology: Line-Interactive, Output power capacity: 1 kVA, Output power: 700 W. AC outlet types: Type F, AC outlets quantity: 8 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 10 min. Form factor: Compact, Product colour: Black, Cooling type: Passive. Certification: CE | Vendor Homepage: <https://cmsstd.tecnoware.com/en-US/Dettaglio/Articolo/453> | Automatic Voltage Regulation (AVR): Yes | Input frequency: 50/60 | Input operation voltage (max): 230 | Noise level: 40 | Number of output phases: 1 | Output frequency: 50/60 | Output operation voltage (max): 230 | Output power: 700 | Output power capacity: 1 | Power factor: 0.7 | Response time: 2 | UPS topology: Line-Interactive | Waveform: Pseudo sine | AC outlet types: Type F | AC outlets quantity: 8 | Battery technology: Sealed Lead Acid (VRLA) | Typical backup time at full load: 10 | Cooling type: Passive | Form factor: Compact | Product colour: Black | Operating altitude: 0 - 3000 | Operating relative humidity (H-H): 0 - 95 | Operating temperature (T-T): 0 - 40 | Certification: CE | Depth: 345 | Height: 100 | Weight: 4400 | Width: 200 | Package depth: 425 | Package height: 146 | Package width: 269 | Units per Pallet: 0 | Units per Shipping Box: 3 | Unit Calculated Volume: 0.02042 | Unit Calculated Weight: 5.83