



IP CAMERA DAHUA IPC- HFW2849S-S-IL- 0280B



Modelis: IPC-HFW2849S-S-IL-0280B

Gamintojas: DAHUA

EAN: 6923172581570

Prekės kodas: 375083

122.98€

Certification: LVD: EN62368-1 EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B 2023-02-22 | Lens viewing angle, diagonal: 132° | Lens viewing angle, vertical: 58° | Lens type: Fixed focal length lens | Number of lenses: 1 | Lens viewing angle, horizontal: 111° | Warnings: Avoid direct contact with water to prevent electrical damage. | Warnings: Ensure that the product is properly installed and protected against falling. | Warnings: The product contains electronic components do not dispose of with the normal household waste. | Bit rate: H.264: 32 kbps-8192 kbps H.265: 12 kbps-8192 kbps | Minimum illumination: 0.008 lx | Back Light Compensation (BLC): Yes | Number of cameras: 1 | Night vision distance: 30 m | White balance: Auto | White balance: Natural | White balance: Outdoor | Ethernet interface type: Fast Ethernet | LED type: IR / White light LED | White balance: Street lamp | Wide Dynamic Range (WDR): 120 dB | White balance: Manual | Camera shutter speed: 1/3 - 1/100000 s | Housing material: Metal | Height: 70 mm | Number of illumination LEDs: 2 | Total megapixels: 8 MP | Internal memory: 256 MB | Highlight Compensation (HLC): Yes | Pan range: 0 - 360° | Depth: 166.2 mm | Ethernet LAN: Yes | Maximum aperture number: 1.6 | Video compression formats: H.264 | Power consumption (Power over Ethernet

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš

įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

(PoE)): 5.9 W | Video compression formats: H.264+ | Supported graphics resolutions: 704 x 576 | Supported graphics resolutions: 1280 x 960 | Supported graphics resolutions: 1280 x 720 | Supported graphics resolutions: 2880 x 1620 | Power consumption (typical): 2.7 W | Mobile operating systems supported: iOS | Progressive scan: Yes | Video compression formats: H.264B | Video compression formats: M-JPEG | Video compression formats: H.264H | DC output voltage: 12 | Closest focusing distance: 1.5 m | Video compression formats: H.265+ | Noise reduction: Yes | Noise reduction technology: 3D noise reduction | Power source type: DC, PoE | Type: IP security camera | Video compression formats: H.265 | Placement supported: External / Internal | Web-based management: Yes | Mounting type: Ceiling/wall | Optical sensor size: 25.4 / 2.7 mm (1 / 2.7") | Operating relative humidity (H-H): 0 - 95% | Video motion detection: Yes | Weight: 470 g | Gain control type: Auto/Manual | Power consumption (max): 5 W | Supported graphics resolutions: 3072 x 2048 | Supported graphics resolutions: 352 x 288 | Maximum resolution: 3840 x 2160 pixels | Supported graphics resolutions: 352 x 240 | Supported graphics resolutions: 2304 x 1296 | Adjustment shutter speed: Auto/Manual | Wi-Fi: No | Supported graphics resolutions: 3840 x 2160 | Supported graphics resolutions: 704 x 480 | Supported graphics resolutions: 2688 x 1520 | Video streaming: Yes | Frame rate: 30 fps | Supported graphics resolutions: 1920 x 1080 | Supported graphics resolutions: 2048 x 1536 (QXGA) | Supported graphics resolutions: 3072 x 1728 | Width: 70 mm | Form factor: Tube/dome | Operating temperature (T-T): -40 - 55 °C | Mobile operating systems supported: Android | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | ROM capacity: 128 MB | Region of Interest (ROI) encoding: Yes | Connectivity technology: Wired | Networking standards: IEEE 802.3af | Product colour: White | Focal length range: 2.8 mm | Number of users: 20 user(s) | Night vision: Yes | Built-in microphone: Yes | Built-in HDD: No | Audio formats supported: G.711a | Sensor type: CMOS | Audio formats supported: G.726 | Audio formats supported: PCM | Audio formats supported: G.711Mu | Web browser: Yes | Bluetooth: No | International Protection (IP) code: IP67 | Number of sensors: 1 | Quality of Service (QoS) support: Yes | Storage temperature (T-T): -40 - 55 °C | Tilt angle range: 0 - 90°

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903