




CASE FAN 120MM/G99.12RS LIN1W3W.00 LIAN LI

Modelis: G99.12RSLIN1W3W.00

Gamintojas: LIAN LI

EAN: 4718466017727

Prekės kodas: 375248

93.99€

SEAMLESS SIGNAL, SMARTER POWER

The UNI FAN SL-INF Wireless is equipped with a wireless receiver with an upgraded 4-pin PWM cable for 12V power delivery and BIOS fan detection. The receiver also has an additional PWM tail cable to ensure stable power.

SYNC THE FANS WITH ONE CONTROLLER

Effortless 2.4GHz wireless control for fan speeds and lighting across up to 10 Lian Li device groups—including SL-INF Wireless, HydroShift II AIOs, Strimer Wireless, and more. Compact and easy to install via rear I/O USB or internal USB 2.0 + PWM header, with each group connected through a PWM-powered receiver for a clean, unified setup.

EFFORTLESS CONTROL, INSTANT RECOGNITION

The UNI FAN SL-INF Wireless simplifies device management with seamless integration via L-Connect. Easily bind individual fans by clicking the link icon, which turns blue once successfully connected.

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

Use the Device Finder to make it light up yellow for 5 seconds for quick identification. The user also can bind all recognized devices at once—streamlining your setup without the hassle of manual configuration.

PERSONALIZED DEVICE MANAGEMENT

Organizing the setup is simple and intuitive through L-Connect 3. Easily rename devices for quick identification—supporting up to 12 English or 6 Chinese characters. Effortlessly rearrange device order using the drag symbol to customize the lighting sequence, meeting future lighting effects flow exactly the way the user needs.

CUSTOMIZE COOLING PROFILE

Simply click on the fan blade area to access the Fan Profile menu and apply preset cooling modes that suit the user's needs. Moreover, the Fan Speed settings for Fan/Pump Profile page allow precise adjustments to fan speed curves and performance—ensuring optimal cooling for both everyday use and intensive workloads.

COMPREHENSIVE CONTROL WITH L-CONNECT 3

Lighting and fan curve management for the UNI FAN SL-INF Wireless is handled with the L-Connect 3 software. Providing built-in presets, easily pick or create a tailored setup for every PC. The L-Connect 3 software provides complete control, ensuring a fully customizable experience.

- Wireless software control for both fan speed and ARGB lighting via L-Connect 3
- Cableless RGB and PWM sync—one receiver per fan cluster, no controller wiring needed
- Triple-zone lighting: blade hub, diffused side strip, and inner edge
- Two different designs on two sides of the fan's frame.
- Receiver can be connected to both sides of the fan.
- Gap between each layer of infinity mirror on the side frames are different to create floating look effect.
- 58 addressable LEDs per fan for immersive lighting effects
- Embedded Fluid Dynamic Bearing (FDB) for superior durability and low-noise operation
- Seamless quick-connect PIN system for fast and clean daisy-chaining
- Compatible with L-Wireless SYNC Controller—control up to 10 fan groups or devices wirelessly

Summary: Lian Li Uni Fan SL-INF WIRELESS 120. Type: All-in-one liquid cooler, Fan diameter: 12 cm,

Rotational speed (min): 0.2 RPM, Rotational speed (max): 2200 RPM, Maximum air pressure: 2.2 mmH2O, Bearing type: Fluid Dynamic Bearing (FDB). Voltage: 12 V. Product colour: White | Vendor Homepage: <https://lian-li.com/product/uni-fan-sl-inf-wireless/> | Bearing type: Fluid Dynamic Bearing (FDB) | Fan diameter: 120 | Maximum air pressure: 2.2 | Maximum airflow: 69.7 | Noise level (high speed): 32.2 | Pulse-width modulation (PWM) support: Yes | Quantity per pack: 1 | Rotational speed (max): 2200 | Rotational speed (min): 0.2 | Suitable location: Computer case, Processor | Type: All-in-one liquid cooler | Fan connector: 4-pin | Illumination colour: Multi | Illumination LED: Yes | Material: Aluminium/Polycarbonate (PC)/Thermoplastic polyester (PBT) | Number of LEDs: 58 | Product colour: White | Fan current: 0.18 | LED voltage: 5 | Power supply: 5.16 | Starting voltage: 6 | Voltage: 12 | Fan dimensions (W x D x H): 120 x 122.1 x 28 | Warranty period: 3 | Model: UNI FAN SL Wireless 120 Reverse Blade | Units per Shipping Box: 20 | Unit Calculated Volume: 0.002918 | Unit Calculated Weight: 0.838