



**UPS
TECNOWARE
840 Watts 1200
VA Wave form
type Modified
sinewave
LineInteractive
Phase 1 phase
FGCERAPL1202SCH**



Modelis: FGCERAPL1202SCH

Gamintojas: TECNOWARE

EAN: 8026475175786

Prekės kodas: 37528

63.98€

- Complete protection against blackout and power surges (overvoltages and undervoltages)
- Recommended for Personal Computers, DVR / NVR and video surveillance systems, ADSL / fiber modem, switch / router, cash registers
- Not suitable with power supplies with Active PFC circuit (Server, PC game, video game console, workstation, Mac computer), lamps and electric motors

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- AVR Automatic Voltage Regulator electronic circuit
- n 2 Italy / Schuko output sockets and n 1 schuko input cable
- outputs socket protected against blackout
- outputs socket protected against overvoltages
- multifunction LED and on-off button
- USB port for UPS control / monitoring and ignition programming / shutdown via Tecnomanager software
- UPS management software TecnoManager compatible with Windows, Mac OS X, Linux etc

Summary: Tecnoware FGCERAPL1202SCH. UPS topology: Standby (Offline), Output power capacity: 1.2 kVA, Output power: 840 W. AC outlet types: Type F, AC outlets quantity: 2 AC outlet(s), USB port type: Micro-USB B. Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 10 min, Typical backup time at half load: 40 min. Form factor: Compact, Product colour: Black, International Protection (IP) code: IP20. Width: 101 mm, Depth: 279 mm, Height: 142 mm | Vendor Homepage: <https://www.tecnoware.com/en-US/Dettaglio/Articolo/55> | Input frequency: 50/60 | Input operation voltage (max): 230 | Input operation voltage (min): 230 | Noise level: 40 | Number of input phases: 1 | Number of output phases: 1 | Output frequency: 50/60 | Output operation voltage (min): 230 | Output power: 840 | Output power capacity: 1.2 | Power factor: 0.7 | UPS topology: Standby (Offline) | AC outlet types: Type F | AC outlets quantity: 2 | USB port: Yes | USB port type: Micro-USB B | Battery technology: Sealed Lead Acid (VRLA) | Typical backup time at full load: 10 | Typical backup time at half load: 40 | Form factor: Compact | International Protection (IP) code: IP20 | Product colour: Black | Operating temperature (T-T): 20 - 25 | Depth: 279 | Height: 142 | Weight: 4500 | Width: 101 | Package depth: 340 | Package height: 220 | Package width: 180 | Units per Shipping Box: 1 | Unit Calculated Volume: 0.01384 | Unit Calculated Weight: 4.75