Switch TP-LINK Switch type Managed Rack mounting Yes 4xRJ-45 ports RJ-45 Ports Type Gigabit Ethernet (10/100/1000) 1xCombo SFP ports quantity 1xSFP module slots quantity Power over Ethernet (PoE) Yes 3xPower over Ethernet plus (PoE+) ports quantity 1xPower over Ethernet 4PPoE

(PoE++) ports quantity Total Power over Ethernet (PoE) budget 120 W IES206GPP

Modelis: IES206GPP

Gamintojas: TP-LINK

EAN: 1210002602051

Prekės kodas: 375295

183.99€

Industrial-Grade Protection Built for Harsh Environments

Enhanced Networking Stability and Security

Easy Operation and Maintenance with Omada's Free Cloud Management

- 4× Gigabit RJ45 Ports (1× PoE++, 3× PoE+)
- 1× Gigabit Combo RJ45/SFP Slot, 1× Gigabit SFP Slot
- 120W Power Budget* with up to 60W for PoE++ Port
- Professional Industrial-Grade Design: -40~75°C Operating Temperature, 6kV Lighting Protection, and 1+1 Redundant Power Input
- Abundant Features: Up to 820ft (250m) PoE,** VLAN, QoS, and STP/RSTP
- Centralized Cloud Management via the Web or Omada App

- Durable IP40 Aluminum Casing and DIN-rail / Wall-mount Design

Summary: TP-Link IES206GPP. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 4. MAC address table: 8000 entries, Switching capacity: 12 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1w, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE.... DC input voltage: 12 - 57 V. Power over Ethernet (PoE). Wall mountable, Rack mounting | Vendor Homepage: https://www.omadanetworks.com/nordic/business-networking/omada-switch-industrial/ies206gpp/ | Switch type: Managed | Basic switching RJ-45 Ethernet ports quantity: 4 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Combo SFP ports quantity: 1 | SFP module slots quantity: 1 | 10G support: No | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Broadcast storm control: Yes | Ethernet LAN data rates: 10,100,1000 | Flow control support: Yes | Link aggregation: Yes | Networking standards: IEEE 802.1D/IEEE 802.1p/IEEE 802.1Q/IEEE 802.1w/IEEE 802.3af/IEEE 802.3at/IEEE 802.3bt/IEEE 802.3x | Port mirroring: Yes | Spanning tree protocol: Yes | Forwarding rate: 8.93 | Jumbo frames: 15000 | Jumbo frames support: Yes | MAC address table: 8000 | Store-and-forward: Yes | Switching capacity: 12 | DHCP features: DHCP client | IGMP snooping: Yes | Multicast support: Yes | DIN rail mounting: Yes | Product colour: Black | Rack mounting: Yes | Wall mountable: Yes | Fanless: Yes | DC input voltage: 12 - 57 | Power source: DC/PoE | Redundant power supply (RPS) support: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) power per port: 30 | Power over Ethernet (PoE) type supported: PoE+/PoE++ (4PPoE) | Power over Ethernet 4PPoE (PoE++) ports quantity: 1 | Power over Ethernet plus (PoE+) ports quantity: 3 | Total Power over Ethernet (PoE) budget: 120 | Operating relative humidity (H-H): 5 - 95 | Operating temperature (T-T): -40 - 75 | Storage relative humidity (H-H): 5 - 95 | Storage temperature (T-T): -40 - 85 | Depth: 120 | Height: 60 | Width: 155 | Quick start guide: Yes | Certification: FCC, CE, RoHS | Model: IES206GPP | Units per Pallet: 0 | Units per Shipping Box: 4 | Unit Calculated Volume: 0.00473 | Unit Calculated Weight: 1.4875