



**UPS
TECNOWARE
665 Watts 950
VA Wave form
type Modified
sinewave Phase
1 phase
FGCERAPL952SCH**

Modelis: FGCERAPL952SCH

Gamintojas: TECNOWARE

EAN: 8026475176370

Prekės kodas: 37558

58.99€

UPS ERA PLUS 950VA, 12V 7Ah battery, It has 1 SCHUKO input fixed cable and 2 SCHUKO outputs protected against blackout, overvoltages and undervoltages. Line Interactive Plus technology. Dimensions 10x14x28 cm, weight 4.2 kg. Equipped with On-Off button with integrated multifunction LED with audible alarm for signaling the operating status. Designed to protect PC Office, DVR for video surveillance, ADSL-Fiber Modem / router, Cash Register. Totally silent.

- Complete protection against blackout and power surges (overvoltages and undervoltages)

Pateikta prekės informacija yra orientacinio pobūdžio. Techninės savybės, nuotraukos, aprašymai ir kaina gali keistis be išankstinio perspėjimo. Gamintojas ir pardavėjas neatsako už galimus duomenų neatitikimus ar tipografines klaidas. Prieš įsigyjant rekomenduojame pasitikrinti aktualią informaciją.

www.shopro.lt | info@shopro.lt | +370 693 39903

- Recommended for Personal Computers, DVR / NVR and video surveillance systems, ADSL / fiber modem, switch / router, cash registers
- Not suitable with power supplies with Active PFC circuit (Server, PC game, video game console, workstation, Mac computer), lamps and electric motors
- AVR Automatic Voltage Regulator electronic circuit
- n 2 Italy / Schuko output sockets and n 1 schuko input cable
- outputs socket protected against blackout
- outputs socket protected against overvoltages
- multifunction LED and on-off button

Summary: Tecnoware Era Plus 950. UPS topology: Line-Interactive, Output power capacity: 0.95 kVA, Output power: 665 W. AC outlet types: Type F, AC outlets quantity: 2 AC outlet(s). Battery technology: Sealed Lead Acid (VRLA), Typical backup time at full load: 10 min. Form factor: Compact, Product colour: Black, International Protection (IP) code: IP20. Compliance certificates: RoHS, Certification: CE | Vendor Homepage: <https://cmsstd.tecnoware.com/en-US/Dettaglio/Articolo/454> | Automatic Voltage Regulation (AVR): Yes | Input frequency: 50/60 | Noise level: 40 | Number of input phases: 1 | Number of output phases: 1 | Output frequency: 50/60 | Output operation voltage (max): 230 | Output operation voltage (min): 230 | Output power: 665 | Output power capacity: 0.95 | Output voltage regulation: 5 | Power factor: 0.7 | Response time: 2 | UPS topology: Line-Interactive | Waveform: Pseudo sine | AC outlet types: Type F | AC outlets quantity: 2 | Battery technology: Sealed Lead Acid (VRLA) | Typical backup time at full load: 10 | Form factor: Compact | International Protection (IP) code: IP20 | LED indicators: Yes | Product colour: Black | Operating altitude: 0 - 3000 | Operating relative humidity (H-H): 0 - 95 | Operating temperature (T-T): 0 - 55 | Certification: CE | Compliance certificates: RoHS | Depth: 279 | Height: 142 | Weight: 4200 | Width: 101 | Package depth: 340 | Package height: 220 | Package width: 180 | Units per Pallet: 0 | Units per Shipping Box: 4 | Unit Calculated Volume: 0.01272 | Unit Calculated Weight: 4.03