

Sharp P701U Standard throw projector 7000 ANSI lumens 3LCD WUXGA (1920x1200) White

Gamintojas: **SHARP** · Modelis: **60006202** · EAN: **4550556180085** · Prekės kodas: **375609**



3 751,90 €

Kaina su PVM

Be PVM: **3 100,74 €**

Neturime



Prekė internetu

Nuskenaukite kodą arba apsilankykite www.shopro.lt

Pagrindinės savybės

- ✓ No filter service required – a completely sealed optical laser LCD engine allows a filter-free design. Brilliant colour brightness is maintained and servicing costs need no longer feature in your budget.
- ✓ Low Noise Level – with 22dB, the silent technology will not disturb your meeting.
- ✓ Future-proof input management – thanks to 4K@30 Hz input processing.
- ✓ No lamp replacement – up to 20,000 h maintenance free operation possible due to Laser Light Source.
- ✓ Risk Group 2 – because of the Risk Group 2 compliance, no prescribed safety precautions are necessary.



Aprašymas

Super silent and brilliantly versatile

Quieter than the tick of a watch, the P701U operates unobtrusively, delivering impressive projection performance without any noise distraction. With 7,000 ANSI lumens, WUXGA resolution, and 4K@30Hz input support, it produces sharp, detailed visuals with consistent clarity even in well-lit environments. Comprehensive connectivity ensures easy integration into a variety of installation scenarios, including meeting rooms, lecture halls, and immersive exhibitions.

Engineered for long-term reliability, the fully sealed optical LCD laser engine provides up to 20,000 hours of maintenance-free performance. With no lamps nor filters to replace, and low power consumption, the P701U combines dependable performance with low operating costs. Risk Group 2 compliance allows for safe operation without prescribed safety precautions, making it a practical choice for professional settings where dependable image quality and quiet performance are priorities.

Techninė specifikacija

Specifications	
Sandėlio grupė	Projector/Plasma > Projector Xga [+0][-0]
Projector	
Projector brightness	7000 ANSI lumens
Projection technology	3LCD
Projector native resolution	WUXGA (1920x1200)
Contrast ratio (typical)	3000000:1
Native aspect ratio	16:10
Screen size compatibility	762 - 7620 mm (30 - 300")
Supported aspect ratios	16:10
Projection distance	0.8 - 12.9 m
Light source	
Light source type	Laser
Service life of light source	20000 h
Lens system	
Focus	Manual
Focal length range	15.3 - 24.6 mm
Aperture range (F-F)	1.6 - 2
Zoom capability	Yes
Zoom type	Manual
Zoom ratio	1.6:1
Horizontal lens shift range	-20 - 20%
Vertical lens shift range	0 - 44%
Video	
Analog signal format system	NTSC, PAL, PAL 60, PAL M, PAL N, SECAM
Full HD	Yes
Ports & interfaces	
HDMI ports quantity	2
Audio (L/R) in	1

Serial interface type	RS-232
Network	
Ethernet LAN	Yes
Ethernet LAN (RJ-45) ports	1
Features	
Noise level	27 dB
Multimedia	
Built-in speaker(s)	Yes
RMS rated power	20 W
Number of built-in speakers	1
Design	
Product type	Standard throw projector
Product colour	White
Display	
Built-in display	No
Power	
Power source	AC
Power consumption (typical)	318 W
Power consumption (standby)	0.3 W
Power consumption (economy mode)	237 W
AC input voltage	100 - 240 V
AC input frequency	50 - 60 Hz
Operational conditions	
Operating temperature (T-T)	5 - 40 °C
Storage temperature (T-T)	-10 - 50 °C
Operating relative humidity (H-H)	20 - 80%
Storage relative humidity (H-H)	20 - 80%
Weight & dimensions	
Weight	9.7 kg
Width	480 mm
Depth	122 mm
Height	407 mm
Packaging content	
Remote control included	Yes

Matmenys ir svoris

Matmenys (I × P × A)	59,00cm × 50,00cm × 27,00cm
----------------------	-----------------------------

Svoris	12,56kg
--------	---------